

## GCC49DRES-S13

## **GCC49DRES-S13** Information

Heisener.com	Part Number Manufacturer Category Description Package	GCC49DRES-S13 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 98POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **GCC49DRES-S13 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows0.062" (1.57mm)FeaturesO.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPolyshor BronzeContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFull BellowsContact TypeSull BellowsContact TypeGid Mount Opening, Unthreaded, 0.125" (3.18mm) DiaColorSide Xour Opening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperaturec65° < 125°C			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions/Bay/Row98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGard Edge, Straddle MountFeaturesSolder Eyclet(s)Contact Material9koptor BronzeContact Finish Thickness30µin (0.76µm)Contact TippeFull BellowsContact TypeBackContact TypeSick MountOpening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperature65°C ~ 125°C	Manufacturer Part Number	GCC49DRES-S13	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountPerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountPorminationSolder Eyelet(s)Contact MaterialOhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-5°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions/Bay/Row98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGujin (0.76µm)Contact TypeFeallellowsContact TypeSolder ScallellowsContact TypeSolder ScallellowsContact TypeSolder ScallellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountPerminationSolder Eyelet(s)Contact FinishGoldContact TypeGoldContact TypeFull BellowsColorBackFaquereSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Series	-	
Number of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountFerminationSolder Eyelet(s)Contact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions     98       Card Thickness     0.062" (1.57mm)       Number of Rows     2       Pitch     0.100" (2.54mm)       Features     Card Extender       Mounting Type     Board Edge, Straddle Mount       Termination     Solder Eyelet(s)       Contact Material     Gold       Contact Finish     Gold       Contact Type     Full Bellows       Color     Black       Flange Feature     Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	49	
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	98	
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeBoard Edge, Straddle MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount	
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)	
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorBlackFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
Color Black   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	$-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
			Report errors?

#### **GCC49DRES-S13** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **GCC49DRES-S13 Payment Methods**



If you have any question about GCC49DRES-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com