

GPM80B

GPM80B Information

	Part Number	GPM80B	
Contraction of the second seco	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	
	Category	Power Supplies - External/Internal (Off-Board) AC DC Converters	
	Description	AC/DC CNVRTR 5V +/-12V -5V 80W	202.14.412.14
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GPM80B Specifications

ManufacturerSL Power Electronics Manufacture of Condor/Ault BrandsCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-Series GGPM80Spries COpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 4-5VVoltage - Output 45VVoltage - Output 412A, 3A, 1A, 1APower (Wats)MedicalApplicationsMedicalVoltage - Isolation-Efficiency70%Operating TemperatureGiustable Output, Remote Sense, Universal InputMounting TypeChasis Mount	-			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesGPM80TypeOpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 4-5VCurrent - Output (Max)12A, 3A, 1A, 1APower (Watts)80W (110W Forced Air)Applications-0Voltage - Isolation-Efficiency70%Operating TemperatureGiustable Output, Remote Sense, Universal InputFeaturesAdjustable Output, Remote Sense, Universal InputMounting Type7.0° L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Manufacturer Part Number	GPM80B		
AC DC Converters Package - Series GPM80 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 -5V Current - Output (Max) 12A, 3A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension 7.00° L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands		
Package-SeriesGPM80TypeOpen FrameNumber of Outputs4Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 212VVoltage - Output 3-12VVoltage - Output 4-5VVoltage - Output 46V(10W Forced Air)Power (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting Type7.0° L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series GPM80 Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 -5V Current - Output (Max) 12A, 3A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature Ajustable Output, Remote Sense, Universal Input Features Adjustable Output, Remote Sense, Universal Input Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)		AC DC Converters		
Type Open Frame Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 -5V Current - Output (Max) 12A, 3A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 0°C ~ 50°C (With Derating) Peatures Adjustable Output, Remote Sense, Universal Input Mounting Type Chasis Mount Size / Dimension 7.0°L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Package	-		
Number of Outputs 4 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 -5V Current - Output (Max) 12A, 3A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00° L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Series	GPM80		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 -5V Current - Output (Max) 12A, 3A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00° L x 4.25° W x 1.86° H (177.8mm x 108.0mm x 47.2mm)	Туре	Open Frame		
Voltage - Output 1 5V Voltage - Output 2 12V Voltage - Output 3 -12V Voltage - Output 4 -5V Current - Output (Max) 12A, 3A, 1A, 1A Power (Watts) 80W (110W Forced Air) Applications Medical Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 50°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.0°L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Number of Outputs	4		
Voltage - Output 212VVoltage - Output 3-12VVoltage - Output 4-5VCurrent - Output (Max)12A, 3A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturessAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-12VVoltage - Output 4-5VCurrent - Output (Max)12A, 3A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 1	5V		
Voltage - Output 4-5VCurrent - Output (Max)12A, 3A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 2	12V		
Current - Output (Max)12A, 3A, 1A, 1APower (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 3	-12V		
Power (Watts)80W (110W Forced Air)ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Output 4	-5V		
ApplicationsMedicalVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)PeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Current - Output (Max)	12A, 3A, 1A, 1A		
NoVoltage - Isolation-Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Power (Watts)	80W (110W Forced Air)		
Efficiency70%Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Applications	Medical		
Operating Temperature0°C ~ 50°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Voltage - Isolation	-		
FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Efficiency	70%		
Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Operating Temperature	0° C ~ 50° C (With Derating)		
Size / Dimension 7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)	Features	Adjustable Output, Remote Sense, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	7.00" L x 4.25" W x 1.86" H (177.8mm x 108.0mm x 47.2mm)		
		Report errors?		

GPM80B Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GPM80B Payment Methods Image: Image

If you have any question about GPM80B, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com