

GTC03032-5P(025)

GTC03032-5P(025) Information

Heisener.com	GTC03032-5P(025) Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RECEPT PNL MT 2POS SIZE 0 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GTC03032-5P(025) Specifications

Manufacturer Part Number GTC03032-5P(025) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Package GT, MIL-5015 Derivative Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert 32-5 Mounting Type Panel Mount, Flange Termination Crimp Reser Bayonet Lock Crimp Shell Size,		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN(Normal)Ingress ProtectionH967 - Dust Tight, WaterproofShell Material, Finish-Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	GTC03032-5P(025)
Circular ConnectorsPackage-SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationIP67 - Dust Tight, WaterproofShell Material, FinishSilverShell Material, FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-Stanting-Statening-Statening-Shell Material, Finish-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense-Statense- <td>Manufacturer</td> <td>Amphenol Industrial Operations</td>	Manufacturer	Amphenol Industrial Operations
Package-SeriesGT, MIL-5015 DerivativeSconector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN(Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishSilverFeaturesSilverVoltage - Rated900VAC, 1250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesGT, MIL-5015 DerivativeConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationIP67 - Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverFeatures-Votage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN(Normal)Ingress ProtectionHPG - Dust Tight, WaterproofShell Material, FinishSilverContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions2Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	GT, MIL-5015 Derivative
Shell Size - Insert32-5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Connector Type	Receptacle, Male Pins
Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	32-5
TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size, MIL	-
Fastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Mounting Type	Panel Mount, Flange
OrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Termination	Crimp
Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Fastening Type	Reverse Bayonet Lock
Shell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Orientation	N (Normal)
Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Ingress Protection	IP67 - Dust Tight, Waterproof
Features-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Material, Finish	Aluminum, Black Zinc Alloy Plated
Voltage - Rated900VAC, 1250VDCCurrent Rating-	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

GTC03032-5P(025) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GTC03032-5P(025) Payment Methods



GTC03032-5P(025) Shipping Methods



If you have any question about GTC03032-5P(025), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com