

HFZ272MBFQH0KR

HFZ272MBFQH0KR Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HFZ272MBFQH0KR Specifications

Manufacturer Part Number HFZ272MBFQH0KR Manufacturer Vishay BC Components Category Capacitors Category Ceramic Capacitors Package Radial, Disc Series Radial, Disc Capacitance 2700pF Tolerance ±20% Voltage - Rated 6000V (6kV) Temperature Coefficient - Operating Temperature 40°C ~ 85°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Nounting Type Inrough Hole Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.492" (12.50mm)		
CategoryCapacitorsPackageRadial, DiscPackageRadial, DiscSeriesHFZCapacitance2700pFTolerance±20%Voltage - Rated6000V (6kV)Temperature Coefficient-Operating Temperature40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Hickth - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)	Manufacturer Part Number	HFZ272MBFQH0KR
Indext Ceramic CapacitorsPackageRadial, DiscSeriesHFZCapacitance2700pFTolerance±20%Voltage - Rated6000V (6kV)Temperature Coefficient-Operating Temperature-40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeRadia, DiscSize / Dimension0.984° Dia (25.00mm)Hight - Seated (Max)-Thickness (Max)-Lead Spacing0.492° (12.50mm)Lead StyleStraight	Manufacturer	Vishay BC Components
PackageRadial, DiscSeriesHFZCapacitance2700pFTolerance±20%Voltage - Rated6000V (6kV)Temperature Coefficient-Operating Temperature40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeNorde HolePackage / CaseRadial, DiscSize / Dimension1.02° (28.00mm)Hight - Seated (Max)-Thickness (Max)-Lead Spacing0.492° (12.50mm)Lead StyleStraight	Category	Capacitors
SeriesHFZCapacitance2700pFTolerance±20%Voltage - Rated600V (6kV)Temperature Coefficient-Operating Temperature40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.984" Dia (25.00mm)High - Seated (Max).102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight		Ceramic Capacitors
Capacitance2700pFTolerance±20%Voltage - Rated6000V (6kV)Temperature Coefficient-Operating Temperature-40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.984" Dia (25.00mm)Hight - Seated (Max)-Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Package	Radial, Disc
Tolerance±20%Voltage - Rated6000V (6kV)Temperature Coefficient-Operating Temperature-40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Series	HFZ
Voltage - Rated6000V (6kV)Temperature Coefficient-Operating Temperature-40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Capacitance	2700pF
Temperature Coefficient-Operating Temperature-40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Tolerance	±20%
Operating Temperature-40°C ~ 85°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Voltage - Rated	6000V (6kV)
FeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Kead StyleStright	Temperature Coefficient	-
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Operating Temperature	-40°C ~ 85°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Features	High Voltage
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Failure Rate	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Mounting Type	Through Hole
Height - Seated (Max)1.102" (28.00mm)Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.492" (12.50mm)Lead StyleStraight	Size / Dimension	0.984" Dia (25.00mm)
Lead Spacing0.492" (12.50mm)Lead StyleStraight	Height - Seated (Max)	1.102" (28.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.492" (12.50mm)
Report errors?	Lead Style	Straight
		Report errors?

HFZ272MBFQH0KR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

HFZ272MBFQH0KR Payment Methods



HFZ272MBFQH0KR Shipping Methods



If you have any question about HFZ272MBFQH0KR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com