

### **HG3-AC48V Information**

Heisener.com

Part Number HG3-AC48V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 20A 48V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HG3-AC48V Specifications**

Manufacturer Part Number         HG3-AC48V           Manufacturer         Panasonic Electric Works           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         HG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         108mA           Coil Voltage         48VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         20A           Switching Voltage         250VAC - Nom           Turn On Voltage (Max)         38.4 VAC           Turn Off Voltage (Min)         14.4 VAC           Operate Time         25ms           Release Time         25ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.250" (6.3mm)   Report errors?		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         HG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         108mA           Coil Voltage         48VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         20A           Switching Voltage         250VAC - Nom           Turn On Voltage (Max)         38.4 VAC           Turn Off Voltage (Min)         14.4 VAC           Operate Time         25ms           Release Time         25ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	HG3-AC48V
Package - Series HG Relay Type General Purpose Coil Type Non Latching Coil Current 108mA Coil Voltage 48VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VAC Turn Off Voltage (Min) 14.4 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Manufacturer	Panasonic Electric Works
Package         -           Series         HG           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         108mA           Coil Voltage         48VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         20A           Switching Voltage         250VAC - Nom           Turn On Voltage (Max)         38.4 VAC           Turn Off Voltage (Min)         14.4 VAC           Operate Time         25ms           Release Time         25ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesHGRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current108mACoil Voltage48VACContact Form3PDT (3 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)38.4 VACTurn Off Voltage (Min)14.4 VACOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 108mA  Coil Voltage 48VAC  Contact Form 3PDT (3 Form C)  Contact Rating (Current) 20A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 38.4 VAC  Turn Off Voltage (Min) 14.4 VAC  Operate Time 25ms  Release Time 25ms  Features  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current108mACoil Voltage48VACContact Form3PDT (3 Form C)Contact Rating (Current)20ASwitching Voltage250VAC - NomTurn On Voltage (Max)38.4 VACTurn Off Voltage (Min)14.4 VACOperate Time25msRelease Time25msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Series	HG
Coil Current         108mA           Coil Voltage         48VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         20A           Switching Voltage         250VAC - Nom           Turn On Voltage (Max)         38.4 VAC           Turn Off Voltage (Min)         14.4 VAC           Operate Time         25ms           Release Time         25ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 48VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 20A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 38.4 VAC Turn Off Voltage (Min) 14.4 VAC Operate Time 25ms Release Time 25ms Features - Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 20A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 38.4 VAC  Turn Off Voltage (Min) 14.4 VAC  Operate Time 25ms  Release Time 25ms  Release Time - 25ms  Features - Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Coil Current	108mA
Contact Rating (Current)  Switching Voltage  250VAC - Nom  Turn On Voltage (Max)  38.4 VAC  Turn Off Voltage (Min)  14.4 VAC  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.250" (6.3mm)	Coil Voltage	48VAC
Switching Voltage  Turn On Voltage (Max)  38.4 VAC  Turn Off Voltage (Min)  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  250VAC - Nom  38.4 VAC  14.4 VAC  25ms  Plug In, Quick Connect - 0.250" (6.3mm)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  14.4 VAC  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  38.4 VAC  14.4 VAC  25ms  25ms  Plug In, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min)  14.4 VAC  Operate Time  25ms  Release Time  25ms  Features  - Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.250" (6.3mm)	Switching Voltage	250VAC - Nom
Operate Time 25ms  Release Time 25ms  Features -  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	38.4 VAC
Release Time 25ms  Features - Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	14.4 VAC
Features -  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Operate Time	25ms
Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Release Time	25ms
Termination Style Plug In, Quick Connect - 0.250" (6.3mm)	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.250" (6.3mm)
		Report errors?

#### **HG3-AC48V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **HG3-AC48V Payment Methods**



















## **HG3-AC48V Shipping Methods**













If you have any question about HG3-AC48V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com