

HSCMRRT100PGSA3

HSCMRRT100PGSA3 Information



For Reference Only

Part Number HSCMRRT100PGSA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**8-SMD, J-Lead, Dual Ports, Same Side

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCMRRT100PGSA3 Specifications

Manufacturer Part Number HSCMRRT100PGSA3 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD		
CategorySensors, TransducersPressure Sensors, TransducersPackage8-SMD, J-Lead, Dual Ports, Same SideSeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD	Manufacturer Part Number	HSCMRRT100PGSA3
Package 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature - 20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package8-SMD, J-Lead, Dual Ports, Same SideSeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD	Category	Sensors, Transducers
SeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD	Package	8-SMD, J-Lead, Dual Ports, Same Side
Operating Pressure Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case Supplier Device Package 8-SMD	Series	TruStability? HSC
Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD	Pressure Type	Vented Gauge
Output Accuracy ±0.25% Voltage - Supply Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Operating Pressure	100 PSI (689.48 kPa)
Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Output Type	SPI
Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Output	12 b
Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Accuracy	±0.25%
Port Style Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Voltage - Supply	3 V ~ 3.6 V
Features Amplified Output, Temperature Compensated Surface Mount Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Port Size	Male - 0.08" (1.93mm) Tube, Dual
Termination Style Surface Mount 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Port Style	Barbed
Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Termination Style	Surface Mount
Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Maximum Pressure	250 PSI (1723.69 kPa)
Supplier Device Package 8-SMD	Operating Temperature	-20°C ~ 85°C
	Package / Case	8-SMD, J-Lead, Dual Ports, Same Side
Report errors?	Supplier Device Package	8-SMD
		Report errors?

HSCMRRT100PGSA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCMRRT100PGSA3 Payment Methods



















HSCMRRT100PGSA3 Shipping Methods













If you have any question about HSCMRRT100PGSA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com