

HY1Z-5V Information



For Reference Only

Part Number HY1Z-5V

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM SPDT 1A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HY1Z-5V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series HY Relay Type Telecom Coil Type Non Latching Coil Current 40mA Coil Voltage SyDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage MovDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Relays Signal Relays, Up to 2 Amps Signal Relays, Up to 2 Amps Signal Relays, Up to 2 Amps Fallows Signal Relays, Up to 2 Amps Amps Signal Relays, Up to 2 Amps Fallows Signal Relays Fallows Fal	-	
Category Relays Signal Relays, Up to 2 Amps Package - Series HY Relay Type Telecom Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 60VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Selease Time Release Time Release Time	Manufacturer Part Number	HY1Z-5V
Package - Series HY Relay Type Telecom Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms	Manufacturer	Panasonic Electric Works
Package - Series HY Relay Type Telecom Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms	Category	Relays
Series HY Relay Type Telecom Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms		Signal Relays, Up to 2 Amps
Relay Type Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) Operate Time Release Time 4ms	Package	-
Coil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage60VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time5msRelease Time4ms	Series	HY
Coil Current 40mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms	Relay Type	Telecom
Coil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage60VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time5msRelease Time4ms	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms	Coil Current	40mA
Contact Rating (Current) Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms	Coil Voltage	5VDC
Switching Voltage 60VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 5ms Release Time 4ms	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 4ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time Sms Release Time 4ms	Switching Voltage	60VDC - Max
Operate Time 5ms Release Time 4ms	Turn On Voltage (Max)	3.75 VDC
Release Time 4ms	Turn Off Voltage (Min)	0.5 VDC
	Operate Time	5ms
0.11.71	Release Time	4ms
Features Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

HY1Z-5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HY1Z-5V Payment Methods



















HY1Z-5V Shipping Methods













If you have any question about HY1Z-5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com