

IF-6-10 Information

Heisener.com

Part Number IF-6-10

Manufacturer Signal Transformer

Category Transformers
Power Transformers

Description XFRMR SEMI-TORO 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IF-6-10 Specifications

Manufacturer Part Number Manufacturer Category Transformers Power Transformers Package - Series IF Type Semi-Toroidal Voltage - Primary Voltage - Secondary (Full Load) Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Seice (Max) Voltage - Isolation Weight Manufacturer IF-6-10 Signal Transformer Transformers Power - Max A Semi-Toroidal It SV, 230V Parallel 5V, Series 10V Parallel 1.2A, Series 600mA Pual Dual Center Tap No For Pin Size / Dimension Size / Dimension 4000Vrms Report errors?		
Category Transformers Package - Series IF Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Manufacturer Part Number	IF-6-10
Package Package Package Primary Poltage - Primary Poltage - Secondary (Full Load) Parallel 5V, Series 10V Primary Winding(s) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Fixed (Max) Power - Seated (Max) Voltage - Secondary Winding Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension For Dim	Manufacturer	Signal Transformer
Package - Series IF Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Category	Transformers
SeriesIFTypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 1.2A, Series 600mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension53.00mm L x 44.00mm WHeight - Seated (Max)22.60mmVoltage - Isolation4000VrmsWeight6.9 lbs (3.1kg)		Power Transformers
Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Fasted (Max) Voltage - Isolation Weight 115V, 230V Parallel 1.2A, Series 600mA Parallel 1.2A, Series 600mA Parallel 1.2A, Series 600mA Parallel 1.2A, Series 600mA Parallel 1.2A, Series 10V Parallel 1.2A, Series	Series	IF
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1.2A, Series 600mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension Fixed (Max) Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 1.2A, Series 600mA Parallel 1.2A, Series 600mA Parallel 1.2A, Series 10V Parallel 1.2A, Series 10V Parallel 1.2A, Series 10V Parallel 1.2A, Series 10V Pual Secondary Winding(s) Dual No 6 VA POP Through Hole PC Pin Size / Dimension 40.00mm L x 44.00mm W 40.00Vrms 40.00Vrms 6.9 lbs (3.1kg)	Туре	Semi-Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Voltage - Isolation Weight Parallel 1.2A, Series 600mA Dual Dual Powal Poul No Powal Po Pin Size / Dimension Size / Onm Voltage - Isolation Voltage - Isolation A000Vrms Parallel 1.2A, Series 600mA Dual Pual No 6 VA A000	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) Voltage - Isolation Weight Dual Au Au Au Au Au Au Au Au Au A	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension53.00mm L x 44.00mm WHeight - Seated (Max)22.60mmVoltage - Isolation4000VrmsWeight6.9 lbs (3.1kg)	Current - Output (Max)	Parallel 1.2A, Series 600mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension53.00mm L x 44.00mm WHeight - Seated (Max)22.60mmVoltage - Isolation4000VrmsWeight6.9 lbs (3.1kg)	Primary Winding(s)	Dual
Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Center Tap	No
Termination Style PC Pin Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Power - Max	6 VA
Size / Dimension 53.00mm L x 44.00mm W Height - Seated (Max) 22.60mm Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 22.60mm 4000Vrms 6.9 lbs (3.1kg)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 6.9 lbs (3.1kg)	Size / Dimension	53.00mm L x 44.00mm W
Weight 6.9 lbs (3.1kg)	Height - Seated (Max)	22.60mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	6.9 lbs (3.1kg)
		Report errors?

IF-6-10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IF-6-10 Payment Methods



















IF-6-10 Shipping Methods













If you have any question about IF-6-10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com