

**IL260-3 Information**


For Reference Only

**Part Number** [IL260-3](#)  
**Manufacturer** NVE Corp/Isolation Products  
**Category** Isolators  
[Digital Isolators](#)  
**Description** DGTL ISO 2.5KV GEN PURP 16SOIC  
**Package** 16-SOIC (0.154", 3.90mm Width)  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**IL260-3 Specifications**

Manufacturer Part Number	<a href="#">IL260-3</a>
Manufacturer	NVE Corp/Isolation Products
Category	Isolators <a href="#">Digital Isolators</a>
Package	16-SOIC (0.154", 3.90mm Width)
Series	IsoLoop?
Technology	GMR (Giant Magnetoresistive)
Type	General Purpose
Isolated Power	No
Number of Channels	5
Inputs - Side 1/Side 2	5/0
Channel Type	Unidirectional
Voltage - Isolation	2500Vrms
Common Mode Transient Immunity (Min)	30kV/μs
Data Rate	110Mbps
Propagation Delay tpLH / tpHL (Max)	15ns, 15ns
Pulse Width Distortion (Max)	3ns
Rise / Fall Time (Typ)	1ns, 1ns
Voltage - Supply	3 V ~ 5.5 V
Operating Temperature	-40°C ~ 85°C
Package / Case	16-SOIC (0.154", 3.90mm Width)
Supplier Device Package	16-SOIC

[Report errors?](#)

## IL260-3 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## IL260-3 Payment Methods



## IL260-3 Shipping Methods



If you have any question about IL260-3, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)