

IPSS-G5002-5C

Request a Quote

IPSS-G5002-5C Information

	Part Number	IPSS-G5002-5C
Comment of the second s	Manufacturer	Cynergy 3
	Category	Sensors, Transducers Pressure Sensors, Transducers
	Description	PRSSR TRNS 0-50BR 4-20MA
	Package	Cylinder
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPSS-G5002-5C Specifications

Manufacturer Cynergy 3 Category Sensors, Transducers Pressure Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series IPSS Operating Pressure Vented Gauge Duptut Type Analog Current Output Type 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 3/4" (19.05mm) BSP Port Style Amplified Output, Temperature Compensated Fermination Style Connector, 4-Pin Maximum Pressure 1450.38 PSI (10000 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder		
CategorySensors, TransducersPressure Sensors, TransducersPackageCylinderSeriesIPSSPressure TypeVented GaugeOperating Pressure725.19 PSI (5000 kPa)Dutput TypeAnalog CurrentDutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFremination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	IPSS-G5002-5C
Pressure Sensors, TransducersPackageCylinderSeriesIPSSPressure TypeVented GaugeOperating Pressure725.19 PSI (5000 kPa)Dutput TypeAnalog CurrentDutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSSPressure TypeVented GaugeDerating Pressure725.19 PSI (5000 kPa)Dutput TypeAnalog CurrentDutput Type4 mA ~ 20 mAAccuracy40.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleFreadedFeaturesConnector, 4-PinPortant Type1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseGylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesIPSSPressure TypeVented GaugeOperating Pressure725.19 PSI (5000 kPa)Dutput TypeAnalog CurrentDutput Operating Pressure4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure725.19 PSI (5000 kPa)Output TypeAnalog CurrentOutput Output4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CasecylinderSupplier Device Package-	Package	Cylinder
Deperating Pressure725.19 PSI (5000 kPa)Dutput TypeAnalog CurrentDutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedFeatures1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Series	IPSS
Dutput TypeAnalog CurrentDutput Type4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedConnector, 4-PinConnector, 4-PinMaximum Pressure1450.38 PSI (1000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Vented Gauge
Dutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Operating Pressure	725.19 PSI (5000 kPa)
Accuracy±0.25%Accuracy9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedPort StyleAmplified Output, Temperature CompensatedFeaturesConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Output Type	Analog Current
Voltage - Supply9 V ~ 32 VPort SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Output	4 mA ~ 20 mA
Port SizeMale - 3/4" (19.05mm) BSPPort StyleThreadedPort StyleAmplified Output, Temperature CompensatedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Voltage - Supply	9 V ~ 32 V
FeaturesAmplified Output, Temperature CompensatedFermination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Port Size	Male - 3/4" (19.05mm) BSP
Termination StyleConnector, 4-PinMaximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Port Style	Threaded
Maximum Pressure1450.38 PSI (10000 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Termination Style	Connector, 4-Pin
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	1450.38 PSI (10000 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 80°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

IPSS-G5002-5C Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSS-G5002-5C Payment Methods





If you have any question about IPSS-G5002-5C, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com