

ISL267817IUZ

ISL267817IUZ Information

For Reference Only	Part Number Manufacturer Category	ISL267817IUZ Renesas Electronics America Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters	
	Description	(ADC) IC ADC 12BIT SPI/SRL 200K 8-MSOP	
	Package	8-TSSOP, 8-MSOP (0.118", 3.00mm Width) For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ISL267817IUZ Specifications

Manufacturer Renesas Electronics America Category Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) Package &-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Number of Bits 12 Sampling Rate (Per Second) 200k Number of Inputs 1 Input Type Differential Data Interface SPI Configuration S/H-ADC Number of A/D Converters 1 Architecture SAR Reference Type External Voltage - Supply, Analog 5V Voltage - Supply, Digital 5V Features - Operating Temperature - Ackage / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-MSOP		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)Package8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Number of Bits12Sampling Rate (Per Second)200kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCNumber of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, AnalogS/VVoltage - Supply, DigitalS/VFeatures-Operating Temperature40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-Conting Type-Supplier Device Package8-MSOPMounting Type-	Manufacturer Part Number	ISL267817IUZ
Data Acquisition - Analog to Digital Converters (ADC)Package8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Number of Bits1Sampling Rate (Per Second)200kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VPeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Manufacturer	Renesas Electronics America
Package8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Number of Bits12Sampling Rate (Per Second)200kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1Reference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Category	Integrated Circuits (ICs)
Series-Number of Bits12Sampling Rate (Per Second)200kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits12Sampling Rate (Per Second)200kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltag - Supply, Analog5VVoltag - Supply, Digital5VPeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Package	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
Sampling Rate (Per Second)200kNumber of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, AnalogSVVoltage - Supply, DigitalSVFeatures-Operating Temperature-Package / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Series	-
Number of Inputs1Input TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Number of Bits	12
Input TypeDifferentialInput TypeDifferentialData InterfaceSPIConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, AnalogSVVoltage - Supply, DigitalSVFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	200k
Part of the second se	Number of Inputs	1
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-Package / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Input Type	Differential
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Data Interface	SPI
Number of A/D Converters1ArchitectureSARArchitectureSARReference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package-Mounting Type-	Configuration	S/H-ADC
ArchitectureSARReference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package6-MSOPMounting Type-	Ratio - S/H:ADC	1:1
Reference TypeExternalVoltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog5VVoltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-	Architecture	SAR
Voltage - Supply, Digital5VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-	Reference Type	External
Features-Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-	Voltage - Supply, Analog	5V
Operating Temperature-40°C ~ 85°CPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-	Voltage - Supply, Digital	5V
Package / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOPMounting Type-	Features	-
Supplier Device Package 8-MSOP Mounting Type -	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
	Supplier Device Package	8-MSOP
Report errors?	Mounting Type	-
		Report errors?

ISL267817IUZ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ISL267817IUZ Payment Methods



ISL267817IUZ Shipping Methods



If you have any question about ISL267817IUZ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com