

ISO7820DWWR

Quote

ISO7820DWWR Information

Joywww.heisener.com	Part Number	ISO7820DWWR	
	Manufacturer	Texas Instruments	
	Category	Isolators Digital Isolators	- 24 K
	Description	DGTL ISO 5.7KV GEN PURP 16SOIC	- <u>126</u> 492
	Package	16-SOIC (0.551", 14.00mm Width)	
		For the pricing/inventory/lead time, please contact	「回うゆう
		us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Q

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ISO7820DWWR Specifications

Manufacturer Part NumberISO7820DWWRManufacturerTexas InstrumentsCategoryIsolatorsDigital IsolatorsDigital IsolatorsPackage16-SOIC (0.551", 14.00mm Width)Series-TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUndirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)4.6nsRise / Fall Time (Typ)2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°CPackage / Case16-SOIC (0.551", 14.00mm Width)	
CategoryIsolatorsPackageDigital IsolatorsPackage16-SOIC (0.551", 14.00mm Width)Series-TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)6ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Digital Isolators Package 16-SOIC (0.551", 14.00mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5700Vrms Common Mode Transient Immunity (Min) 100kV/µs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) Ifons Pulse Width Distortion (Max) 4.6ns Kise / Fall Time (Typ) 2.4ns, 2.4ns Voltage - Supply 0.25 V ~ 5.5 V Operating Temperature -55°C ~ 125°C	
Package16-SOIC (0.551", 14.00mm Width)Series-TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.55 VOperating Temperature55°C ~ 125°C	
Series-TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
TechnologyCapacitive CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply.55°C ~ 125°C	
Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5700Vrms Common Mode Transient Immunity (Min) 100kV/μs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 4.6ns Pulse Width Distortion (Max) 2.4ns, 2.4ns No 2.25 V ~ 5.5 V Operating Temperature -55°C ~ 125°C	
Isolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.55 VOperating Temperature-55°C ~ 125°C	
Number of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsKise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply0.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.25 V ~ 5.5 VVoltage - Supply-55°C ~ 125°C	
Channel TypeUnidirectionalVoltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Voltage - Isolation5700VrmsCommon Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Common Mode Transient Immunity (Min)100kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Data Rate100MbpsPropagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Propagation Delay tpLH / tpHL (Max)16ns, 16nsPulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Pulse Width Distortion (Max)4.6nsRise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Rise / Fall Time (Typ)2.4ns, 2.4nsVoltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Voltage - Supply2.25 V ~ 5.5 VOperating Temperature-55°C ~ 125°C	
Operating Temperature-55°C ~ 125°C	
Package / Case 16-SOIC (0.551", 14.00mm Width)	
Supplier Device Package 16-SOIC	
Rep	Report errors?

ISO7820DWWR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ISO7820DWWR Payment Methods





If you have any question about ISO7820DWWR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com