



J0006D01BNL Information

www.nessener.com

For Reference Only

Part Number J0006D01BNL

Manufacturer Pulse Electronics Network
Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 100 BASE-TX

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









J0006D01BNL Specifications

Manufacturer J0006D01BNL Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J0 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C Report errors?		
Canectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? J0 Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.545" (13.84mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Features Board Guide Tab Direction Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature Contact Timperature	Manufacturer Part Number	J0006D01BNL
Package-SeriesPULSEJACK? JOConnector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	Pulse Electronics Network
Package-SeriesPULSEJACK? JOConnector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Category	Connectors, Interconnects
SeriesPULSEJACK? JOConnector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Package	-
Number of Ports1Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Series	PULSEJACK? J0
Number of Rows1Applications10/100 Base-TX, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board LED Color Number of Cores per Jack Shielding Features Board Guide Tab Direction Contact Material Phosphor Bronze Contact Finish Operating Temperature 10/100 Base-TX, AutoMDIX Through Hole 70/100 Base-TX, AutoMDIX Auto	Number of Ports	1
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100 Base-TX, AutoMDIX
Termination Solder Height Above Board 0.545" (13.84mm) LED Color Green - Yellow Number of Cores per Jack 4 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board LED Color Green - Yellow Number of Cores per Jack Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0.545" (13.84mm) 6reen - Yellow 4 A A A A A A A A A A A A	Orientation	90° Angle (Right)
LED ColorGreen - YellowNumber of Cores per Jack4ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 4 Contact Material April 1 O°C ~ 70°C	Height Above Board	0.545" (13.84mm)
Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Green - Yellow
Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	4
Tab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Shielding	Shielded
Contact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Features	Board Guide
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Down
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

J0006D01BNL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

J0006D01BNL Payment Methods





















J0006D01BNL Shipping Methods













If you have any question about J0006D01BNL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com