



JC1A1B-DC24V Information

Heisener.com

Part Number JC1A1B-DC24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JC1A1B-DC24V Specifications

Manufacturer Part NumberJC1A1B-DC24VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJCRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current41.6mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)19.2 VDC
Category Relays Power Relays, Over 2 Amps Package - Series JC Relay Type General Purpose Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) Switching Voltage 250VAC - Max
Package - Series JC Relay Type General Purpose Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) Switching Voltage 250VAC - Max
Package - Series JC Relay Type General Purpose Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Series JC Relay Type General Purpose Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Relay Type Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) Switching Voltage 250VAC - Max
Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Coil Current 41.6mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Contact Rating (Current) 5A Switching Voltage 250VAC - Max
Switching Voltage 250VAC - Max
Turn On Voltage (Max) 19.2 VDC
Turn Off Voltage (Min) 2.4 VDC
Operate Time 15ms
Release Time 2ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

JC1A1B-DC24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JC1A1B-DC24V Payment Methods



















JC1A1B-DC24V Shipping Methods













If you have any question about JC1A1B-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com