

# JCH-18R

### **JCH-18R Information**



Part Number	JCH-18R	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CARTRIDGE NON STD	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

# For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **JCH-18R Specifications**

AnufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCHSeries TypeCartridgeCurrent Rating390AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-ApplicationsIndicatingFeaturesIndicatingClassRApprovalsUROperating Temperature50kAPackage / CaseSolou" StandardPackage / CaseCartridge, Non-StandardSize / DimensionSizou" StandardSize / DimensionSizou" StandardSize / DimensionSizou" Standard		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCHFuse TypeCartridgeCurrent Rating390AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Manufacturer Part Number	JCH-18R
Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCHFuse TypeCartridgeCurrent Rating390AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature50kABreaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesJCHFuse TypeCartridgeFuse TypeCartridgeCurrent Rating390AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseSu00" Dia x 10.880" L (76.20mm x 276.35mm)	Category	Circuit Protection
SeriesJCHFuse TypeCartridgeCurrent Rating390AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / Case3.000" Dia x 10.880" L (76.20mm x 276.35mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating390AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature50kABreaking Capacity @ Rated Voltage50kAMounting TypeCartridge, Non-StandardPackage / Case3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Package	Cartridge, Non-Standard
Current Rating390ACurrent Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3,000" Dia x 10.880" L (76.20mm x 276.35mm)	Series	JCH
Voltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Current Rating	390A
Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Voltage Rating - AC	2400V (2.4kV)
ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovalsUROperating Temperature>0kABreaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Voltage Rating - DC	-
IndicatingFeaturesIndicatingClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Response Time	-
ClassRApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Applications	Motor Protection
ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Class	R
Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Approvals	UR
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 3.000" Dia x 10.880" L (76.20mm x 276.35mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 10.880" L (76.20mm x 276.35mm)
		Report errors?

#### **JCH-18R Guarantees**



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about JCH-18R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com