

JCX-20E

JCX-20E Information



Part Number	JCX-20E	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CARTRIDGE NON STD	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



JCX-20E Specifications

Manufacturer Eaton Gaton Electrical Package Cartridge, Non-Standard Series Gatrridge, Non-Standard Series JCX Fuse Type Cartridge Current Rating 20A Voltage Rating - AC 2400V (2.4kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Approvals - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Satridge, Non-Standard Size / Dimension 2.100" Dia x 9.500" L (53.34mm x 241.30mm)		
CategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCXFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Manufacturer Part Number	JCX-20E
Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesJCXFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature50kABreaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesJCXFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Type-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Category	Circuit Protection
SeriesJCXFuse TypeCartridgeCurrent RatingCoAVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingerClassEApprovals-Operating Temperature50kABreaking Capacity @ Rated Voltage50kAMounting TypeCartridge, Non-StandardPackage / Case2.100" Dia x 9.500" L (53.34mm x 241.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating20AVoltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature50kABreaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Package	Cartridge, Non-Standard
Current Rating20ACurrent Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Series	JCX
Voltage Rating - AC2400V (2.4kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Current Rating	20A
Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Voltage Rating - AC	2400V (2.4kV)
ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Voltage Rating - DC	-
IndicatingFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Response Time	-
ClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Applications	Transformer Protection
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Class	Е
Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Approvals	-
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 2.100" Dia x 9.500" L (53.34mm x 241.30mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	2.100" Dia x 9.500" L (53.34mm x 241.30mm)
		Report errors?

JCX-20E Guarantees



If you have any question about JCX-20E, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com