

JJN-25 Information

Heisener.com

Part Number JJN-25
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 25A 300VAC/160VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JJN-25 Specifications

Manufacturer Part NumberJJN-25ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesLimitron? JJNFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 0.880" L (10.41mm x 22.35mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesLimitron? JJNFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Manufacturer Part Number	JJN-25
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesLimitron? JJNFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesLimitron? JJNFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Category	Circuit Protection
SeriesLimitron? JJNFuse TypeCartridgeCurrent Rating25AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 0.880" L (10.41mm x 22.35mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 25A Voltage Rating - AC 300V Voltage Rating - DC 160V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension CEACSA Cartridge Ca	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 160V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 25A 300V 26A 20V 20V 40V 40V 40V 40V 40V 40V	Series	Limitron? JJN
Voltage Rating - AC Voltage Rating - DC 160V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 160V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 160V Fast Fast CE, CSA CE, CSA, UL CE, CSA, UL CE, CSA, UL COPRATION TO THE COMMON TO	Current Rating	25A
Response Time Applications Electrical, Industrial Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial CE, CSA, UL CE, CSA, UL	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Voltage Rating - DC	160V
Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.410" Dia x 0.880" L (10.41mm x 22.35mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.410" Dia x 0.880" L (10.41mm x 22.35mm)
		Report errors?

JJN-25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JJN-25 Payment Methods



















JJN-25 Shipping Methods













If you have any question about JJN-25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com