

### JJN-60 Information



For Reference Only

Part Number JJN-60 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 60A 300VAC/160VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JJN-60 Specifications**

Manufacturer Part NumberJJN-60ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesLimitron? JJNFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 0.880" L (14.22mm x 22.35mm)Report errors?		
Category Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series Limitron? JJN Fuse Type Cartridge Current Rating 60A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cirruit Protection Electrical, Specialty Fuses  Cartridge, Non-Standard Size / Dimension  Cirridge, Non-Standard Size / Dimension	Manufacturer Part Number	JJN-60
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series Limitron? JJN  Fuse Type Cartridge  Current Rating 60A  Voltage Rating - AC 300V  Voltage Rating - DC 160V  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesLimitron? JJNFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Category	Circuit Protection
SeriesLimitron? JJNFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC300VVoltage Rating - DC160VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 0.880" L (14.22mm x 22.35mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 60A Voltage Rating - AC 300V Voltage Rating - DC 160V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cason Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension COA COA CARTRIDGE CARTRIDGE COA Cartridge Car	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 300V Voltage Rating - DC 160V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 60A	Series	Limitron? JJN
Voltage Rating - AC  Voltage Rating - DC  160V  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  300V  300V  300V  300V  400  400  Fast  CE, CSA  Cleverical, Industrial  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COPRATION OF COMMON OF CO	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  160V  Fast Fast Fast  Ce, CSA  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COPRATION OF TABLE OF TAB	Current Rating	60A
Response Time Fast  Applications Electrical, Industrial  Features - Class T  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Voltage Rating - DC	160V
Features - Class T   Approvals CE, CSA, UL   Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC   Mounting Type Holder   Package / Case Cartridge, Non-Standard   Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.560" Dia x 0.880" L (14.22mm x 22.35mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 0.880" L (14.22mm x 22.35mm)
		Report errors?

#### JJN-60 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **JJN-60 Payment Methods**





















## **JJN-60 Shipping Methods**













If you have any question about JJN-60, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com