

JLLS100.V Information

Manufa Categor

Part NumberJLLS100.VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 100A 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JLLS100.V Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension JERESTOR SERVICE Circuit Protection Electrical, Industrial CE, CSA, UL Operating Temperature Bolt Mount CE, CSA, UL Cylindrical, Blade Terminal (Bolt) Size / Dimension Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage COUKA Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	JLLS100.V
Beaking Capacity @ Rated Voltage Flectrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) POWR-GARD? JLLS Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? JLLS Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Category	Circuit Protection
SeriesPOWR-GARD? JLLSFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassTApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 1.642" L (20.60mm x 41.70mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 100A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canonical Additional Additio	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 100A 600V 600V 600V 600V 600V 600V 600V 6	Series	POWR-GARD? JLLS
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V Fast Fast CE, CSA CE, CSA, UL CE, CSA, UL CE, CSA, UL COJENTATE OF CONTROL OF CON	Current Rating	100A
Response Time Applications Electrical, Industrial Features - Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Features - Clextical, Industrial Features - CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPITATION CONTROL CON	Voltage Rating - AC	600V
Applications Features - Class T Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial CE, CSA, UL CE, CSA, UL BOLT CE, CSA, UL CONSTITUTE OF CONSTITUT	Voltage Rating - DC	300V
Features - Class T T CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Response Time	Fast
Class T Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA, UL CUSA, U	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Class	T
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.811" Dia x 1.642" L (20.60mm x 41.70mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.811" Dia x 1.642" L (20.60mm x 41.70mm)
		Report errors?

JLLS100.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JLLS100.V Payment Methods

































If you have any question about JLLS100.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com