

JM1AN-TMP-DC48V-F

JM1AN-TMP-DC48V-F Information



For Reference Only

Part Number JM1AN-TMP-DC48V-F Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 20A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JM1AN-TMP-DC48V-F Specifications

Manufacturer Part NumberJM1AN-TMP-DC48V-FManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.75mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.75mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	JM1AN-TMP-DC48V-F
Package - Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Turn On Voltage (Max) Through Hole	Manufacturer	Panasonic Electric Works
Package - Series JM Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Turnout Hole	Category	Relays
SeriesJMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current18.75mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Package	-
Coil TypeNon LatchingCoil Current18.75mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)20ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Series	JM
Coil Current Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 20A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Current	18.75mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Voltage	48VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time 20ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Switching Voltage	250VAC - Max
Operate Time20msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Turn On Voltage (Max)	33.6 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	4.8 VDC
Features Sealed - Flux Protection Mounting Type Through Hole	Operate Time	20ms
Mounting Type Through Hole	Release Time	10ms
	Features	Sealed - Flux Protection
Termination Style PC Pin, Quick Connect - 0.250" (6.3mm)	Mounting Type	Through Hole
	Termination Style	PC Pin, Quick Connect - 0.250" (6.3mm)
Report errors?		Report errors?

JM1AN-TMP-DC48V-F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JM1AN-TMP-DC48V-F Payment Methods



















JM1AN-TMP-DC48V-F Shipping Methods













If you have any question about JM1AN-TMP-DC48V-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com