



JMGAPD-26M Information



For Reference Only

Part Number JMGAPD-26M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 26.5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JMGAPD-26M Specifications

Manufacturer Part NumberJMGAPD-26MManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysPackage-SeriesMilitary, MIL-R-39016/18, MGA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesMilitary, MIL-R-39016/18, MGA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JMGAPD-26M
Package-SeriesMilitary, MIL-R-39016/18, MGA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-R-39016/18, MGA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesMilitary, MIL-R-39016/18, MGA, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28 VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 17mA Coil Voltage 26.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Series	Military, MIL-R-39016/18, MGA, CII
Coil Current17mACoil Voltage26.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage28VDC - NomTurn On Voltage (Max)14.2 VDCTurn Off Voltage (Min)1.37 VDCOperate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 26.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style DPDT (2 Form C) 1A A Series Series Sevent Series S	Coil Current	17mA
Contact Rating (Current) Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	26.5VDC
Switching Voltage 28VDC - Nom Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 14.2 VDC Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) 1.37 VDC Operate Time 2ms Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	28VDC - Nom
Operate Time2msRelease Time4msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	14.2 VDC
Release Time 4ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.37 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	2ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	Sealed - Hermetically
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

JMGAPD-26M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JMGAPD-26M Payment Methods



















JMGAPD-26M Shipping Methods













If you have any question about JMGAPD-26M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com