



JR25WR-4P(74) Information

Heisener.com

Part Number JR25WR-4P(74)

Manufacturer Hirose Electric Co Ltd

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 4POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JR25WR-4P(74) Specifications

Manufacturer Part NumberJR25WR-4P(74)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsPackage-SeriesJR-WConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert25Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67/68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Brass, Black Chromium PlatedContact FinishSilverFeatures-Voltage - Rated300VAC, 420VDCCurrent Rating30AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesJR-WConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert25Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67/68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Brass, Black Chromium PlatedContact FinishSilverFeatures-Voltage - Rated300VAC, 420VDCCurrent Rating30A	Manufacturer Part Number	JR25WR-4P(74)
Package-SeriesJR-WConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert25Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67/68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Brass, Black Chromium PlatedContact FinishSilverFeatures-Voltage - Rated300VAC, 420VDCCurrent Rating30A	Manufacturer	Hirose Electric Co Ltd
Package-SeriesJR-WConnector TypeReceptacle, Male PinsNumber of Positions4Shell Size - Insert25Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67/68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Brass, Black Chromium PlatedContact FinishSilverFeatures-Voltage - Rated300VAC, 420VDCCurrent Rating30A	Category	Connectors, Interconnects
Series JR-W Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 25 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A		Circular Connectors
Connector Type Receptacle, Male Pins Number of Positions 4 Shell Size - Insert 25 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Package	-
Number of Positions4Shell Size - Insert25Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67/68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Brass, Black Chromium PlatedContact FinishSilverFeatures-Voltage - Rated300VAC, 420VDCCurrent Rating30A	Series	JR-W
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features Voltage - Rated 300VAC, 420VDC Current Rating 30A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Number of Positions	4
Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Shell Size - Insert	25
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Shell Size, MIL	-
Fastening Type Threaded Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Mounting Type	Panel Mount, Flange
Orientation Keyed Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Termination	Solder Cup
Ingress Protection IP67/68 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Brass, Black Chromium Plated Contact Finish Silver Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Brass, Black Chromium Plated Silver - 300VAC, 420VDC 30A	Orientation	Keyed
Contact Finish Features Voltage - Rated Current Rating Silver - 300VAC, 420VDC 30A	Ingress Protection	IP67/68 - Dust Tight, Waterproof
Features - Voltage - Rated 300VAC, 420VDC Current Rating 30A	Shell Material, Finish	Aluminum Alloy, Brass, Black Chromium Plated
Voltage - Rated 300VAC, 420VDC Current Rating 30A	Contact Finish	Silver
Current Rating 30A	Features	-
	Voltage - Rated	300VAC, 420VDC
Report errors?	Current Rating	30A
		Report errors?

JR25WR-4P(74) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JR25WR-4P(74) Payment Methods





















JR25WR-4P(74) Shipping Methods













If you have any question about JR25WR-4P(74), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com