

## JTN1AS-PA-F-DC18V

### JTN1AS-PA-F-DC18V Information



For Reference Only

Part Number JTN1AS-PA-F-DC18V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 30A 18V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## JTN1AS-PA-F-DC18V Specifications

Manufacturer Part Number     JTN1AS-PA-F-DC18V       Manufacturer     Panasonic Electric Works       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     JT-N       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     44.4mA       Coil Voltage     18VDC       Contact Form     SPST-NO (1 Form A)       Contact Rating (Current)     30A       Switching Voltage     277VAC - Max       Turn On Voltage (Max)     13.5 VDC       Turn Off Voltage (Min)     1.8 VDC       Operate Time     20ms       Release Time     10ms       Features     Insulation - Class F, Sealed - Fully       Mounting Type     Through Hole       Termination Style     PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage18VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	JTN1AS-PA-F-DC18V
Package-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage18VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage18VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesJT-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage18VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current44.4mACoil Voltage18VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage277VAC - MaxTurn On Voltage (Max)13.5 VDCTurn Off Voltage (Min)1.8 VDCOperate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	JT-N
Coil Current Coil Voltage 18VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 277VAC - Max Turn On Voltage (Max) 13.5 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 20ms Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 18VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 277VAC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.8 VDC  Operate Time 20ms  Release Time 10ms  Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 277VAC - Max  Turn On Voltage (Max) 13.5 VDC  Turn Off Voltage (Min) 1.8 VDC  Operate Time 20ms  Release Time 10ms  Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	44.4mA
Contact Rating (Current)  Switching Voltage  277VAC - Max  Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	18VDC
Switching Voltage  Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style  277VAC - Max  13.5 VDC  1.8 VDC  1.8 VDC  20ms  PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  13.5 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	30A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  10ms  Features  Insulation - Class F, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	277VAC - Max
Operate Time20msRelease Time10msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	13.5 VDC
Release Time 10ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.8 VDC
Features Insulation - Class F, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
X X		Report errors?

#### JTN1AS-PA-F-DC18V Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## JTN1AS-PA-F-DC18V Payment Methods



















## JTN1AS-PA-F-DC18V Shipping Methods













If you have any question about JTN1AS-PA-F-DC18V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com