

## **JVN1AF-100V Information**

Heisener.com

Part Number JVN1AF-100V

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 16A 100V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **JVN1AF-100V Specifications**

Manufacturer Part NumberJVN1AF-100VManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)60 VDCTurn Off Voltage (Min)4 VDCOperate Time8msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		
CategoryRelaysPackage-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)60 VDCTurn Off Voltage (Min)4 VDCOperate Time8msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	JVN1AF-100V
Package - Series JV-N Relay Type General Purpose Coil Type Non Latching Coil Current 6mA Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 60 VDC Turn Off Voltage (Min) 4 VDC Operate Time 8ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trous SPST-NO (1 Form Sealer Sealed - Flux Protection Through Hole	Manufacturer	Panasonic Electric Works
Package-SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)60 VDCTurn Off Voltage (Min)4 VDCOperate Time8msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Category	Relays
SeriesJV-NRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)60 VDCTurn Off Voltage (Min)4 VDCOperate Time8msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 6mA  Coil Voltage 100VDC Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 277VAC, 30VDC - Max  Turn On Voltage (Max) 60 VDC  Turn Off Voltage (Min) 4 VDC  Operate Time 8ms  Release Time 5ms  Features Sealed - Flux Protection Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 6mA Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 60 VDC Turn Off Voltage (Min) 4 VDC Operate Time 8ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Series	JV-N
Coil Current Coil Voltage 100VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 60 VDC Turn Off Voltage (Min) 4 VDC Operate Time 8ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 100VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 277VAC, 30VDC - Max  Turn On Voltage (Max) 60 VDC  Turn Off Voltage (Min) 4 VDC  Operate Time 8ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 277VAC, 30VDC - Max  Turn On Voltage (Max) 60 VDC  Turn Off Voltage (Min) 4 VDC  Operate Time 8ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole	Coil Current	6mA
Contact Rating (Current)  Switching Voltage  277VAC, 30VDC - Max  Turn On Voltage (Max)  60 VDC  Turn Off Voltage (Min)  4 VDC  Operate Time  8ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole	Coil Voltage	100VDC
Switching Voltage 277VAC, 30VDC - Max  Turn On Voltage (Max) 60 VDC  Turn Off Voltage (Min) 4 VDC  Operate Time 8ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  8ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole	Contact Rating (Current)	16A
Turn Off Voltage (Min)  Operate Time  8ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole	Switching Voltage	277VAC, 30VDC - Max
Operate Time 8ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn On Voltage (Max)	60 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	4 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole	Operate Time	8ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **JVN1AF-100V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **JVN1AF-100V Payment Methods**



















## **JVN1AF-100V Shipping Methods**













If you have any question about JVN1AF-100V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com