

JW1AFSN-B-DC24V

JW1AFSN-B-DC24V Information



For Reference Only

Part Number JW1AFSN-B-DC24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JW1AFSN-B-DC24V Specifications

| Manufacturer Part NumberJW1AFSN-B-DC24VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | | |
|--|--------------------------|--------------------------------------|
| CategoryRelaysPackage-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Manufacturer Part Number | JW1AFSN-B-DC24V |
| Package-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Manufacturer | Panasonic Electric Works |
| Package-SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Category | Relays |
| SeriesJWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | | Power Relays, Over 2 Amps |
| Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Package | - |
| Coil TypeNon LatchingCoil Current22mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Series | JW |
| Coil Current Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Relay Type | General Purpose |
| Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Coil Type | Non Latching |
| Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Coil Current | 22mA |
| Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Release Time Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Coil Voltage | 24VDC |
| Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Contact Form | SPST-NO (1 Form A) |
| Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Contact Rating (Current) | 10A |
| Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Switching Voltage | 250VAC, 30VDC - Max |
| Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Turn On Voltage (Max) | 16.8 VDC |
| Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 2.4 VDC |
| Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Operate Time | 15ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 5ms |
| Termination Style PC Pin | Features | Insulation - Class B, Sealed - Fully |
| | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

JW1AFSN-B-DC24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JW1AFSN-B-DC24V Payment Methods



















JW1AFSN-B-DC24V Shipping Methods













If you have any question about JW1AFSN-B-DC24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com