

JWS503 Information

Heisener.com

Part Number JWS503

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 3.3V 50W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JWS503 Specifications

Manufacturer JWS503 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Manufacturer Part Number	JWS503
Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Category	Power Supplies - External/Internal (Off-Board)
Series JWS Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Series	JWS
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Size / Dimension 3.3V	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output 4 - Current - Output (Max) - Adjustable Output, DC Input Capable, PFC, Universal Input Chassis Mount 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - Universal Input Chassis Mount 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Voltage - Output 1	3.3V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 10A 10A 10A 10A 10B 10C 10C 10C 10C 10C 10C 10C	Voltage - Output 3	-
Power (Watts) 50W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Current - Output (Max)	10A
Voltage - Isolation 3kV (3000V) Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Power (Watts)	50W
Efficiency 65% Operating Temperature -10°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension -10°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, PFC, Universal Input Chassis Mount 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Efficiency	65%
Mounting Type Chassis Mount Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Operating Temperature	-10° C ~ 60° C (With Derating)
Size / Dimension 6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	6.25" L x 3.35" W x 1.45" H (158.8mm x 85.1mm x 36.8mm)
1		Report errors?

JWS503 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JWS503 Payment Methods



















JWS503 Shipping Methods













If you have any question about JWS503, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com