

JY0-0016NL Information



For Reference Only

Part Number JY0-0016NL

Manufacturer Pulse Electronics Network Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics CONN MAGJACK 1PORT 100 BASE-TX

Description

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









JY0-0016NL Specifications

Manufacturer Part Number JY0-0016NL Manufacturer Pulse Electronics Network Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? JY Connector Type RJ45 with USB A, Dual Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C		
Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series PULSEJACK? JY Connector Type RJ45 with USB A, Dual Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature	Manufacturer Part Number	JY0-0016NL
Package-SeriesPULSEJACK? JYConnector TypeRJ45 with USB A, DualNumber of Ports1Number of Rows1Applications10/100 Base-TXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.170" (29.72mm)LED ColorGreen, Orange - YellowNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	Pulse Electronics Network
Package - Series PULSEJACK? JY Connector Type RJ45 with USB A, Dual Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Category	Connectors, Interconnects
SeriesPULSEJACK? JYConnector TypeRJ45 with USB A, DualNumber of Ports1Number of Rows1Applications10/100 Base-TXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.170" (29.72mm)LED ColorGreen, Orange - YellowNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector Type RJ45 with USB A, Dual Number of Ports 1 Number of Rows 1 Applications 10/100 Base-TX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Package	-
Number of Ports1Number of Rows1Applications10/100 Base-TXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.170" (29.72mm)LED ColorGreen, Orange - YellowNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Series	PULSEJACK? JY
Number of Rows1Applications10/100 Base-TXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.170" (29.72mm)LED ColorGreen, Orange - YellowNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45 with USB A, Dual
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Operating Temperature 10/100 Base-TX Through Hole Green, Orage - Manuel Solder 1.170" (29.72mm) 1.17	Number of Ports	1
Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100 Base-TX
Termination Solder Height Above Board 1.170" (29.72mm) LED Color Green, Orange - Yellow Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board LED Color Green, Orange - Yellow Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature	Orientation	90° Angle (Right)
LED ColorGreen, Orange - YellowNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 5 Shielded, EMI Finger Board Lock Up Core	Height Above Board	1.170" (29.72mm)
Shielding Shielded, EMI Finger Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	LED Color	Green, Orange - Yellow
Features Board Lock Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	5
Tab DirectionUpContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Shielding	Shielded, EMI Finger
Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Features	Board Lock
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Up
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
D	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$
Report errors?		Report errors?

JY0-0016NL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

JY0-0016NL Payment Methods





















JY0-0016NL Shipping Methods













If you have any question about JY0-0016NL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com