

K272M15X7RH5TL2

K272M15X7RH5TL2 Information

Part Number K272M15X7RH5TL2

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 2700PF 100V X7R RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

www.flaiseger.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









K272M15X7RH5TL2 Specifications

Manufacturer Part Number K272M15X7RH5TL2 Manufacturer Vishay BC Components Category Capacitors Package Radial Series Mono-Kap? K Capacitance 2700pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.060" (1.58mm)		
Category Capacitors Package Radial Series Mono-Kap? K Capacitance 2700pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Manufacturer Part Number	K272M15X7RH5TL2
PackageCeramic CapacitorsPackageRadialSeriesMono-Kap? KCapacitance2700pFTolerance±20%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)	Manufacturer	Vishay BC Components
PackageRadialSeriesMono-Kap? KCapacitance2700pFTolerance±20%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)	Category	Capacitors
Series Mono-Kap? K Capacitance 2700pF Tolerance ±20% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)		Ceramic Capacitors
Capacitance2700pFTolerance±20%Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)	Package	Radial
Tolerance ±20% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Series	Mono-Kap? K
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)	Capacitance	2700pF
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension X7R A7R A7R A7R A7R - B7R - COE - COE	Tolerance	±20%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Voltage - Rated	100V
Features - Case	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Applications	General Purpose
Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Failure Rate	-
Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm)	Mounting Type	Through Hole
	Package / Case	Radial
Height - Seated (Max) 0.062" (1.58mm)	Size / Dimension	0.157" L x 0.098" W (4.00mm x 2.50mm)
1101ght 50400 (1141)	Height - Seated (Max)	0.062" (1.58mm)
Thickness (Max) -	Thickness (Max)	-
Lead Spacing 0.098" (2.50mm)	Lead Spacing	0.098" (2.50mm)
Lead Style Straight	Lead Style	Straight
Report errors?		Report errors?

K272M15X7RH5TL2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

K272M15X7RH5TL2 Payment Methods



















K272M15X7RH5TL2 Shipping Methods













If you have any question about K272M15X7RH5TL2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com