


K391J15C0GK5TH5

K391J15C0GK5TH5 Information



For Reference Only

Part Number K391J15C0GK5TH5

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 390PF 200V C0G/NP0 RAD

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









K391J15C0GK5TH5 Specifications

Manufacturer Part NumberK391J15COGK5TH5ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialSeriesMono-Kap? KCapacitance390pFTolerance±5%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)0.100" (2.54mm)		
Category Capacitors Package Radial Series Mono-Kap? K Capacitance 390pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Manufacturer Part Number	K391J15C0GK5TH5
Package Radial Series Mono-Kap? K Capacitance 390pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Manufacturer	Vishay BC Components
PackageRadialSeriesMono-Kap? KCapacitance390pFTolerance±5%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-	Category	Capacitors
Series Mono-Kap? K Capacitance 390pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -		Ceramic Capacitors
Capacitance 390pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Package	Radial
Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Series	Mono-Kap? K
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-	Capacitance	390pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension O.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) Thickness (Max) - COG, NPO COG, NPO COG, NPO COG, NPO Cogneral Purpose Fallure Rade - O.100" (2.54mm) Thickness (Max) - COG, NPO COGN COG, NPO COGN CO	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension O.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) Thickness (Max) -	Voltage - Rated	200V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Applications	General Purpose
Package / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.100" (2.54mm)Thickness (Max)-	Failure Rate	-
Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.100" (2.54mm) Thickness (Max) -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) 0.100" (2.54mm) -	Package / Case	Radial
Thickness (Max)	Size / Dimension	0.157" L x 0.098" W (4.00mm x 2.50mm)
	Height - Seated (Max)	0.100" (2.54mm)
0.107# (5.00)	Thickness (Max)	-
Lead Spacing U.19/ (5.00mm)	Lead Spacing	0.197" (5.00mm)
Lead Style Formed Leads	Lead Style	Formed Leads
Report errors?		Report errors?

K391J15C0GK5TH5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

K391J15C0GK5TH5 Payment Methods



















K391J15C0GK5TH5 Shipping Methods













If you have any question about K391J15C0GK5TH5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com