



KAL25FBR750 Information

Heisener.com

Part Number KAL25FBR750

Manufacturer Stackpole Electronics Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 0.75 OHM 1% 25W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KAL25FBR750 Specifications

Manufacturer Part NumberKAL25FBR750ManufacturerStackpole Electronics Inc.CategoryResistorsPackageAxial, BoxSeriesKALResistance750 mOhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)		
CategoryResistorsPackageAxial, BoxSeriesKALResistance750 mOhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)	Manufacturer Part Number	KAL25FBR750
Chassis Mount Resistors Axial, Box Series KAL Resistance 750 mOhms Tolerance ±1% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) Oxage Axial, Box Axial Axial	Manufacturer	Stackpole Electronics Inc.
PackageAxial, BoxSeriesKALResistance750 mOhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)	Category	Resistors
SeriesKALResistance750 mOhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)		Chassis Mount Resistors
Resistance750 mOhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)	Package	Axial, Box
Tolerance $\pm 1\%$ Power (Watts) $25W$ CompositionWirewoundTemperature Coefficient $\pm 50 \mathrm{ppm/^{\circ}C}$ Operating Temperature $-55^{\circ}\mathrm{C} \sim 275^{\circ}\mathrm{C}$ FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.062^{\circ}\mathrm{L} \times 1.080^{\circ}\mathrm{W} (26.97 \mathrm{mm} \times 27.43 \mathrm{mm})$ Height - Seated (Max) $0.577^{\circ}\mathrm{(14.66 \mathrm{mm})}$	Series	KAL
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm)	Resistance	750 mOhms
CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.062'' \text{L x } 1.080'' \text{W } (26.97 \text{mm x } 27.43 \text{mm})$ Height - Seated (Max) $0.577'' (14.66 \text{mm})$	Tolerance	$\pm 1\%$
Temperature Coefficient ± 50 ppm/°C Operating Temperature -55 °C ~ 275 °C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062 " L x 1.080 " W $(26.97$ mm x 27.43 mm) Height - Seated (Max) 0.577 " $(14.66$ mm)	Power (Watts)	25W
Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $1.062^{\circ}\text{L x } 1.080^{\circ}\text{W } (26.97\text{mm x } 27.43\text{mm})$ Height - Seated (Max) $0.577^{\circ} (14.66\text{mm})$	Composition	Wirewound
Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm)	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm)	Operating Temperature	-55°C ~ 275°C
Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm)	Features	Moisture Resistant
Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm)	Coating, Housing Type	Aluminum
Height - Seated (Max) 0.577" (14.66mm)	Mounting Feature	Flanges
-	Size / Dimension	1.062" L x 1.080" W (26.97mm x 27.43mm)
[] (] (] ()	Height - Seated (Max)	0.577" (14.66mm)
Lead Style Solder Lugs	Lead Style	Solder Lugs
Package / Case Axial, Box	Package / Case	Axial, Box
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

KAL25FBR750 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KAL25FBR750 Payment Methods



















KAL25FBR750 Shipping Methods













If you have any question about KAL25FBR750, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com