

KHU-11A12-120 Information



For Reference Only

Part Number KHU-11A12-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHU-11A12-120 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 13ms Release Time KHU Relays Relays Power Relays, Over 2 Amps Power Relays, Over 2 Amps Power Relays Power Relays Power Relays Power Relays Power Relays Amps Power Relays Power Relays		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6ms	Manufacturer Part Number	KHU-11A12-120
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms	Category	Relays
SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6ms		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms	Package	-
Coil TypeNon LatchingCoil Current11mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6ms	Series	KHU
Coil Current Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms	Coil Type	Non Latching
Contact Form C DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms	Coil Current	11mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms	Coil Voltage	120VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms	Switching Voltage	240VAC - Max
Operate Time 13ms Release Time 6ms	Turn On Voltage (Max)	102 VAC
Release Time 6ms	Turn Off Voltage (Min)	-
	Operate Time	13ms
T 1.1 CL D	Release Time	6ms
Features Insulation - Class B	Features	Insulation - Class B
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

KHU-11A12-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHU-11A12-120 Payment Methods

































If you have any question about KHU-11A12-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com