

KRP-C-900SP Information

Part Number KRP-C-900SP

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 900A 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KRP-C-900SP Specifications

Manufacturer Part NumberKRP-C-900SPManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Blade Terminal (Bolt)SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating900AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating900AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Manufacturer Part Number	KRP-C-900SP
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series LOW-PEAK? KRP-C Fuse Type Cartridge Current Rating 900A Voltage Rating - AC Voltage Rating - DC Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Electrical, Industrial Features - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Size / Dimension Electrical, Industrial Features - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesLOW-PEAK? KRP-CFuse TypeCartridgeCurrent Rating900AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage300kA AC, 100kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Category	Circuit Protection
Series LOW-PEAK? KRP-C Fuse Type Cartridge Current Rating 900A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2000A		Electrical, Specialty Fuses
Fuse Type Current Rating 900A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Converting Capacity @ States (Capacity & Capacity	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 900A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2000 300kA ac (500 m bx 3.750" L (63.50mm x 95.25mm)	Series	LOW-PEAK? KRP-C
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300V Slow Slow Electrical, Industrial - L CE, CSA, UL CE	Current Rating	900A
Response Time Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Slow Slow Slow Slow Slow Slow Slow CE, CSA, UL CE	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Voltage Rating - DC	300V
Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension L CE, CSA, UL - CE	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Class	L
Breaking Capacity @ Rated Voltage 300kA AC, 100kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Breaking Capacity @ Rated Voltage	300kA AC, 100kA DC
Size / Dimension 2.500" Dia x 3.750" L (63.50mm x 95.25mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.500" Dia x 3.750" L (63.50mm x 95.25mm)
		Report errors?

KRP-C-900SP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KRP-C-900SP Payment Methods



















KRP-C-900SP Shipping Methods













If you have any question about KRP-C-900SP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com