

# KTPS24-05040MP

#### **KTPS24-05040MP Information**

www.heisener.com	 KTPS24-05040MP Volgen America/Kaga Electronics USA Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC WALL MOUNT ADAPTER 5V 20W - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **KTPS24-05040MP Specifications**

ManufacturerVolgen America/Kaga Electronics USACategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesKTPS24Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input5VVoltage - Output (Max)4APower (Watts)20WPower (Watts)20WPolarization-ApplicationsFil (Commercial)ApplicationsTE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBartel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm		
CategoryPower Supplies - External/Internal (Off-Board) AC DC Desktop, Wall AdaptersPackage-SeriesKTPS24Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Manufacturer Part Number	KTPS24-05040MP
AC DC Desktop, Wall AdaptersPackage-SeriesKTPS24Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Manufacturer	Volgen America/Kaga Electronics USA
Package-SeriesKTPS24Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug. 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series KTPS24   Region Utilized International   Form Wall Mount   Input Type Multi-Blade (Included)   Voltage - Input 100 ~ 240 VAC   Voltage - Output 5V   Current - Output (Max) 4A   Power (Watts) 20W   No Load Power Consumption -   Polarization Positive Center   Applications ITE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm x 40.5mm)	Package	-
FormWall MountInput TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COperating Temperature0°C ~ 40°CStiz / Dimension3.05" L x 2.04" W x 1.55" H (77.5mm x 40.5mm)	Series	KTPS24
Innut TypeMulti-Blade (Included)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Region Utilized	International
Voltage - Input 100 ~ 240 VAC   Voltage - Output 5V   Current - Output (Max) 4A   Power (Watts) 20W   No Load Power Consumption -   Polarization Positive Center   Applications ITE (Commercial)   Efficiency Level V   Operating Temperature 0°C ~ 40°C   Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Form	Wall Mount
Voltage - Output5VCurrent - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Input Type	Multi-Blade (Included)
Current - Output (Max)4APower (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)20WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Voltage - Output	5V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 40.5mm)	Current - Output (Max)	4A
PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Power (Watts)	20W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	No Load Power Consumption	-
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Polarization	Positive Center
Operating Temperature 0°C ~ 40°C   Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm   Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Efficiency	Level V
Size / Dimension 3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)	Operating Temperature	$0^{\circ}C \sim 40^{\circ}C$
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	3.05" L x 2.04" W x 1.59" H (77.5mm x 51.8mm x 40.5mm)
		Report errors?

#### **KTPS24-05040MP** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **KTPS24-05040MP Payment Methods**





If you have any question about KTPS24-05040MP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com