



KUL-5D15D-24 Information

Heisener.com

Part Number KUL-5D15D-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUL-5D15D-24 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package Series KUL Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features Insulation - Class B		
Category Relays Power Relays, Over 2 Amps Package - Series KUL Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 24VVAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 25ms Release Time Power Relays Relays Relays Relays Relays Analogs Latching, Over 2 Amps Amps Latching Latching Latching, Dual Coil Latching	Manufacturer Part Number	KUL-5D15D-24
Package - Series KUL Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - KUL Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Coperate Time 25ms Release Time 25ms	Category	Relays
SeriesKULRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current-Coil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time25msRelease Time25ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms	Package	-
Coil Type Latching, Dual Coil Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms	Series	KUL
Coil Current - Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms	Relay Type	General Purpose
Coil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time25msRelease Time25ms	Coil Type	Latching, Dual Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms	Coil Current	-
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms	Coil Voltage	24VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 25ms Release Time 25ms	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms	Switching Voltage	240VAC - Max
Operate Time 25ms Release Time 25ms	Turn On Voltage (Max)	18 VDC
Release Time 25ms	Turn Off Voltage (Min)	-
	Operate Time	25ms
Features Insulation - Class B	Release Time	25ms
	Features	Insulation - Class B
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

KUL-5D15D-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUL-5D15D-24 Payment Methods



















KUL-5D15D-24 Shipping Methods













If you have any question about KUL-5D15D-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com