



KUMP-7D58-36 Information



For Reference Only

Part Number KUMP-7D58-36

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 15A 36V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KUMP-7D58-36 Specifications

Manufacturer KUMP-7D58-36 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series KUMP Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 36VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 27 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKUMPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage36VDCContact FormDPST (2 Form A)Contact Rating (Current)15ASwitching Voltage277VAC - MaxTurn On Voltage (Max)27 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Manufacturer Part Number	KUMP-7D58-36
Package-SeriesKUMPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage36VDCContact FormDPST (2 Form A)Contact Rating (Current)15ASwitching Voltage277VAC - MaxTurn On Voltage (Max)27 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KUMP Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 36VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 27 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesKUMPRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage36VDCContact FormDPST (2 Form A)Contact Rating (Current)15ASwitching Voltage277VAC - MaxTurn On Voltage (Max)27 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 36VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 27 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 36VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 27 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Series	KUMP
Coil Current33.3mACoil Voltage36VDCContact FormDPST (2 Form A)Contact Rating (Current)15ASwitching Voltage277VAC - MaxTurn On Voltage (Max)27 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time10msFeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 36VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 27 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style DPST (2 Form A) 15A 15A 277VAC - Max 27 VDC 10ms 15ms 10ms 1	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 7 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style 15A 27VAC - Max 27 VDC 15ms	Coil Voltage	36VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 27 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Switching Voltage	277VAC - Max
Operate Time 15ms Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	27 VDC
Release Time 10ms Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Operate Time	15ms
Mounting Type Chassis Mount Termination Style Quick Connect - 0.187" (4.7mm)	Release Time	10ms
Termination Style Quick Connect - 0.187" (4.7mm)	Features	Insulation - Class B
·	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.187" (4.7mm)
report errors.		Report errors?

KUMP-7D58-36 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KUMP-7D58-36 Payment Methods



















KUMP-7D58-36 Shipping Methods













If you have any question about KUMP-7D58-36, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com