

# L225J750

## L225J750 Information



Part Number	L225J750	
Manufacturer	Ohmite	
Category	Resistors Chassis Mount Resistors	
Description	RES CHAS MNT 750 OHM 5% 225W	
Package	Radial, Tubular	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## L225J750 Specifications

ManufacturerOhmiteCategoryResistorsChassis Mount ResistorsPackageRadial, TubularSeries270Resistance750 OhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COpprating TemperatureFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting Feature1.126" Dia x 10.500" L (28.60mm x 266.70mm)Size / Dimension.Height - Seated (Max)-Package / CaseRadial, Tubular		
CategoryResistorsPackageRadial, TubularPackageRadial, TubularSeries270Resistance750 OhmsTolerance±5%Power (Watts)225WCompositionWirewoundTomperature Coefficient±260ppm/°COperating TemperatureFalme Retardant Coating, SafetyCoating, Housing TypeHirewound LoadedSize / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsFaiture RateRadial, TubularFaiture Rate-Faiture RateSolder Lugs	Manufacturer Part Number	L225J750
Chassis Mount ResistorsPackageRadial, TubularSeries270Resistance750 OhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260pm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126° Dia x 10.500° L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer	Ohmite
PackageRadial, TubularSeries270Resistance750 OhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeNitreous Enamel CoatedMounting Feature1.126° Dia x 10.500° L (28.60mm x 266.70mm)Kieght - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Failure Rate- <tr< td=""><td>Category</td><td>Resistors</td></tr<>	Category	Resistors
Series270Resistance750 OhmsTolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension.1126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance750 OhmsTolerance±5%Power (Watts)22SWCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance±5%Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension.126° Dia x 10.500° L (28.60mm x 266.70mm)Height - Seated (Max).Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate.	Series	270
Power (Watts)225WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Resistance	750 Ohms
CompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Tolerance	±5%
Temperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Power (Watts)	225W
Operating Temperature-55°C ~ 350°CFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Composition	Wirewound
FeaturesFlame Retardant Coating, SafetyFeaturesFlame Retardant Coating, SafetyCoating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Temperature Coefficient	$\pm 260 \text{ppm}^{\circ}\text{C}$
Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Operating Temperature	-55°C ~ 350°C
Mounting FeatureBrackets (not included)Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Features	Flame Retardant Coating, Safety
Size / Dimension1.126" Dia x 10.500" L (28.60mm x 266.70mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.126" Dia x 10.500" L (28.60mm x 266.70mm)
Package / Case Radial, Tubular   Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

#### L225J750 Guarantees



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about L225J750, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com