

L25S005.T Information

Meisener.com

Part Number L25S005.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 5A 250VAC/DC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









L25S005.T Specifications

| Manufacturer L25S005.T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 5A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | | |
|--|-----------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 5A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical | Manufacturer Part Number | L25S005.T |
| Package Cartridge, Non-Standard Series POWR-GARD? L25S Fuse Type Cartridge Current Rating 5A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Easter SA POWR-GARD? L25S Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Manufacturer | Littelfuse Inc. |
| PackageCartridge, Non-StandardSeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Category | Circuit Protection |
| SeriesPOWR-GARD? L25SFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 5A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension CSOV Cartridge Car | Package | Cartridge, Non-Standard |
| Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5A 250V 250V Response Time Fast Semiconductors - CE, CSA, UR - CE, CSA, UR - COBA DC Holder Cartridge, Non-Standard Size / Dimension 510 510 510 510 510 510 510 51 | Series | POWR-GARD? L25S |
| Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V 26 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V East 250V Ea | Current Rating | 5A |
| Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Semiconductors - CE, CSA, UR | Voltage Rating - AC | 250V |
| Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Semiconductors - Semiconductors - CE, CSA, UR - CE, CSA, UR - Holder - Cartridge, Non-Standard 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Voltage Rating - DC | 250V |
| Features - Class - Class - CE, CSA, UR - CE, CSA, UR Operating Temperature - Comparing Capacity @ Rated Voltage 200kA AC, 20kA DC Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Response Time | Fast |
| Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Applications | Semiconductors |
| Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UR - CUR - CUR - CUR - CONNA - CONNA - CUR - CONNA - CONNA - CUR - CONNA - CONN | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Class | - |
| Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Approvals | CE, CSA, UR |
| Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Operating Temperature | - |
| Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Breaking Capacity @ Rated Voltage | 200kA AC, 20kA DC |
| Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) | Mounting Type | Holder |
| · · · · · · · · · · · · · · · · · · · | Package / Case | Cartridge, Non-Standard |
| Report errors? | Size / Dimension | 0.563" Dia x 2.000" L (14.30mm x 50.80mm) |
| | | Report errors? |

L25S005.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

L25S005.T Payment Methods



















L25S005.T Shipping Methods













If you have any question about L25S005.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com