

L717TWB13W3PMP3SV4FRM6 Information

Contact service class serv	 L717TWB13W3PMP3SV4FRM6 Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 13POS R/A SOLDER - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



L717TWB13W3PMP3SV4FRM6 Specifications

Manufacturer Part NumberL717TWB13W3PMP3SV4FRM6ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsD-sub ConnectorsD-sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions3 (10 + 3 Power)Number of Rows2Schell Size, Connector LayoutSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)Flange FeatureSolderForturesSolderSchell Material, FinishGoldContact Finish ThicknessGoldIngress Protection-Atterial Flammability Rating-Material Flammability Rating-Material Flammability Rating-		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Manufacturer Part Number	L717TWB13W3PMP3SV4FRM6
D-Sub ConnectorsPackage-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.4µm)Ingress Protection-Material Flammability Rating-	Manufacturer	Amphenol Commercial Products
Package-SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesSodderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flanmability Rating-	Category	Connectors, Interconnects
SeriesTWConnector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-		D-Sub Connectors
Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Package	-
Connector TypePlug, Male PinsNumber of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishGoldContact Finish ThicknessI6µin (0.40µm)Ingress Protection-Material Flammability Rating-	Series	TW
Number of Positions13 (10 + 3 Power)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Connector Style	D-Sub, Combo
Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Connector Type	Plug, Male Pins
Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Number of Positions	13 (10 + 3 Power)
Contact TypeSignal and PowerMounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Atterial Flammability Rating-	Number of Rows	2
Mounting TypePanel Mount, Through Hole, Right AngleFlange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Shell Size, Connector Layout	3 (DB, B) - 13C3, 13W3
Flange FeatureMating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessI6µin (0.40µm)Ingress Protection-Material Flammability Rating-	Contact Type	Signal and Power
TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Mounting Type	Panel Mount, Through Hole, Right Angle
FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Flange Feature	Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Termination	Solder
Contact FinishGoldContact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Features	Board Lock, Grounding Indents, Mounting Brackets
Contact Finish Thickness16µin (0.40µm)Ingress Protection-Material Flammability Rating-	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability Rating-	Contact Finish	Gold
Material Flammability Rating -	Contact Finish Thickness	16μin (0.40μm)
	Ingress Protection	-
	Material Flammability Rating	-
Report errors?		Report errors?

L717TWB13W3PMP3SV4FRM6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

L717TWB13W3PMP3SV4FRM6 Payment Methods



If you have any question about L717TWB13W3PMP3SV4FRM6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com