

LA6595T-TLM-E

LA6595T-TLM-E Information



rt Number	LA6595T-TLM-E	
nufacturer	ON Semiconductor	
tegory	Integrated Circuits (ICs) PMIC - Full, Half-Bridge Drivers	
scription	IC MOTOR DRIVER ON/OFF 8MSOP	
ckage	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LA6595T-TLM-E Specifications

ManufacturerON SemiconductorCategoryIntegrated Circuits (ICs) PMIC - Full, Half-Bridge DriversPackage8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Output ConfigurationHalf Bridge (2)ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load-Operating Temperature-Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)		
CategoryIntegrated Circuits (ICs)PMIC - Full, Half-Bridge DriversPackage&-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Output ConfigurationHalf Bridge (2)ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply.2 V ~ 14 VVoltage - Load.30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Manufacturer Part Number	LA6595T-TLM-E
PMIC - Full, Half-Bridge DriversPackage8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Output ConfigurationHalf Bridge (2)ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveBipolarBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Output / Channel500mAVoltage - Supply2.2 V ~ 14 VVoltage - Supply-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Manufacturer	ON Semiconductor
Package8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Output ConfigurationHalf Bridge (2)ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load-Operating Temperature-30°C ~ 90°C (TA)Features-Full ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-MSOP (0.118", 3.00mm Width)	Category	Integrated Circuits (ICs)
Series-Output ConfigurationHalf Bridge (2)ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load-Sorc ~ 90°C (TA)-Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP		PMIC - Full, Half-Bridge Drivers
Output ConfigurationHalf Bridge (2)ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load-Operating Temperature-Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-MSOP (0.118", 3.00mm Width)	Package	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
ApplicationsDC Motors, General PurposeInterfaceLogicLoad TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load-Operating Temperature-Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Series	-
InterfaceLogicLodat TypeInductiveTechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load2.2 V ~ 14 VOperating Temperature-Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)	Output Configuration	Half Bridge (2)
Load TypeInductiveLoad TypeBipolarTechnology-Rds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load2.2 V ~ 14 VOperating Temperature-Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Applications	DC Motors, General Purpose
TechnologyBipolarRds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load2.2 V ~ 14 VOperating Temperature-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Interface	Logic
Rds On (Typ)-Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load2.2 V ~ 14 VOperating Temperature-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Load Type	Inductive
Current - Output / Channel500mACurrent - Peak Output-Voltage - Supply2.2 V ~ 14 VVoltage - Load2.2 V ~ 14 VOperating Temperature-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Technology	Bipolar
Current - Peak Output-Voltage - Supply $2.2 V ~ 14 V$ Voltage - Load $2.2 V ~ 14 V$ Operating Temperature $-30^{\circ}C ~ 90^{\circ}C$ (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Rds On (Typ)	-
Voltage - Supply2.2 V ~ 14 VVoltage - Load2.2 V ~ 14 VOperating Temperature-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Current - Output / Channel	500mA
Voltage - Load2.2 V ~ 14 VOperating Temperature-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Current - Peak Output	-
Operating Temperature-30°C ~ 90°C (TA)Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Voltage - Supply	2.2 V ~ 14 V
Features-Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Voltage - Load	2.2 V ~ 14 V
Fault ProtectionOver TemperatureMounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Operating Temperature	-30°C ~ 90°C (TA)
Mounting TypeSurface MountPackage / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Features	-
Package / Case8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Supplier Device Package8-MSOP	Fault Protection	Over Temperature
Supplier Device Package 8-MSOP	Mounting Type	Surface Mount
	Package / Case	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
Report errors?	Supplier Device Package	8-MSOP
1 × 1		Report errors?

LA6595T-TLM-E Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LA6595T-TLM-E Payment Methods



LA6595T-TLM-E Shipping Methods



If you have any question about LA6595T-TLM-E, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com