

LEA150F-30-R

equest a Quote

LEA150F-30-R Information

| Heisener.com | Part Number | LEA150F-30-R |
|--------------------|--------------|---|
| | Manufacturer | Cosel USA, Inc. |
| | Category | Power Supplies - External/Internal (Off-Board) AC DC Converters |
| | Description | AC/DC PS (OPEN FRAME) |
| | Package | - |
| | | For the pricing/inventory/lead time, please contact |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LEA150F-30-R Specifications

| ManufacturerCosel USA, Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 130VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 45APower (Watts)ITE (Commercial)Voltage - Isolation3kV (300V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesKemote On/Off, Universal InputMounting TypeChassis Mount | _ | | | |
|--|--------------------------|---|--|--|
| CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 130VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 45APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (300V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeSa, Yu 1, 4, 5, W 1, 1, 6, H (222, 0mm x 75, 0mm x 37, 0mm) | Manufacturer Part Number | LEA150F-30-R | | |
| AC DC Converters Package - Series LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation SA Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Manufacturer | Cosel USA, Inc. | | |
| Package-SeriesLEATypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 130VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 45APower (Wats)150WApplicationsITE (Commercial)Voltage - Isolation3v(3000V)Efficiency8%Operating Temperature-o°C ~ 0°C (With Derating)FeaturesRemote On/Off, Universal InputMounting Type6Asis MountSize / Dimension8.4" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Category | Power Supplies - External/Internal (Off-Board) | | |
| Kein LEA Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W Voltage - Isolation XV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type SA;* L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | | AC DC Converters | | |
| Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation SA Voltage - Isolation ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Package | - | | |
| Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Series | LEA | | |
| Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Туре | Open Frame | | |
| Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W Applications ITE (commercial) Voltage - Isolation 3KV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type S.4" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Number of Outputs | 1 | | |
| Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 87% Operating Temperature -20°C ~ 70°C (With Derating) Features Remote On/Off, Universal Input Mounting Type Chassis Mount Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Input | 85 ~ 264 VAC | | |
| Voltage - Output 3-Voltage - Output 4-Current - Output (Max)5APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Output 1 | 30V | | |
| Voltage - Output 4-Current - Output (Max)5APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Output 2 | - | | |
| Current - Output (Max)5APower (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 37.0mm) | Voltage - Output 3 | - | | |
| Power (Watts)150WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Output 4 | - | | |
| ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Current - Output (Max) | 5A | | |
| Voltage - Isolation3kV (3000V)Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Power (Watts) | 150W | | |
| Efficiency87%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Applications | ITE (Commercial) | | |
| Operating Temperature-20°C ~ 70°C (With Derating)FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Voltage - Isolation | 3kV (3000V) | | |
| FeaturesRemote On/Off, Universal InputMounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Efficiency | 87% | | |
| Mounting TypeChassis MountSize / Dimension8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Operating Temperature | $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) | | |
| Size / Dimension 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | Features | Remote On/Off, Universal Input | | |
| | Mounting Type | Chassis Mount | | |
| Report errors? | Size / Dimension | 8.74" L x 2.95" W x 1.46" H (222.0mm x 75.0mm x 37.0mm) | | |
| | | Report errors? | | |

LEA150F-30-R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LEA150F-30-R Payment Methods



LEA150F-30-R Shipping Methods



If you have any question about LEA150F-30-R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com