



LKS1J332MESZ Information

Heisener.com

For Reference Only

Part Number LKS1J332MESZ

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3300UF 20% 63V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LKS1J332MESZ Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series LKS Capacitance 3300μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series LKS Capacitance 3300µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	LKS1J332MESZ
Package Radial, Can - Snap-In Series LKS Capacitance 3300μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	Nichicon
Package Radial, Can - Snap-In Series LKS Capacitance 3300µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series LKS Capacitance 3300µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 3300μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	LKS
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Capacitance	3300μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 8	Voltage - Rated	63V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency 2.45A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	Audio
Impedance - Care Spacing 0.394" (10.00mm) 0.866" Dia (22.00mm) 0.866" Dia (22.00mm) 1.378" (35.00mm) 0.876 Care Mount Land Size - Care Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	2.45A @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.378" (35.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.378" (35.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

LKS1J332MESZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LKS1J332MESZ Payment Methods





















LKS1J332MESZ Shipping Methods













If you have any question about LKS1J332MESZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com