



### **LM4041CFTA Information**



For Reference Only

Part Number LM4041CFTA
Manufacturer Diodes Incorporated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

**Description** IC VREF SHUNT 1.225V SOT23 **Package** TO-236-3, SC-59, SOT-23-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **LM4041CFTA Specifications**

Manufacturer Part Number         LM4041CFTA           Manufacturer         Diodes Incorporated           Category         Integrated Circuits (ICs)           Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         1.225V           Voltage - Output (Max)         -           Current - Output         12mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         20μVrms           Voltage - Input         -           Current - Supply         -           Current - Supply         -           Current - Supply         -           Urrent - Cathode         68μA           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23		
Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         1.225V           Voltage - Output (Max)         -           Current - Output         12mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         20μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         68μA           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23	Manufacturer Part Number	LM4041CFTA
Package         PMIC - Voltage Reference           Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         1.225V           Voltage - Output (Max)         -           Current - Output         12mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         20μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         68μA           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23	Manufacturer	Diodes Incorporated
Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         1.225V           Voltage - Output (Max)         -           Current - Output         12mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         20μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         68μA           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23	Category	Integrated Circuits (ICs)
Series         -           Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         1.225V           Voltage - Output (Max)         -           Current - Output         12mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         20μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         68μA           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23		PMIC - Voltage Reference
Reference Type         Shunt           Output Type         Fixed           Voltage - Output (Min/Fixed)         1.225V           Voltage - Output (Max)         -           Current - Output         12mA           Tolerance         ±0.5%           Temperature Coefficient         100ppm/°C           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         20μVrms           Voltage - Input         -           Current - Supply         -           Current - Cathode         68μA           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23	Package	TO-236-3, SC-59, SOT-23-3
Output TypeFixedVoltage - Output (Min/Fixed) $1.225$ VVoltage - Output (Max)-Current - Output $12mA$ Tolerance $\pm 0.5\%$ Temperature Coefficient $100ppm/^{\circ}C$ Noise - $0.1$ Hz to $10$ Hz-Noise - $10$ Hz to $10$ kHz $20\mu$ VrmsVoltage - Input-Current - Supply-Current - Cathode $68\mu$ AOperating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TA)Mounting TypeSurface MountPackage / Case $TO-236-3$ , SC-59, SOT-23-3Supplier Device PackageSOT-23	Series	-
Voltage - Output (Min/Fixed)       1.225 V         Voltage - Output (Max)       -         Current - Output       12mA         Tolerance       ±0.5%         Temperature Coefficient       100ppm/°C         Noise - 0.1Hz to 10Hz       -         Noise - 10Hz to 10kHz       20μVrms         Voltage - Input       -         Current - Supply       -         Current - Cathode       68μA         Operating Temperature       -40°C ~ 125°C (TA)         Mounting Type       Surface Mount         Package / Case       TO-236-3, SC-59, SOT-23-3         Supplier Device Package       SOT-23	Reference Type	Shunt
Voltage - Output (Max)-Current - Output12mATolerance±0.5%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz20μVrmsVoltage - Input-Current - Supply-Current - Cathode68μAOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Output Type	Fixed
Current - Output       12mA         Tolerance       ±0.5%         Temperature Coefficient       100ppm/°C         Noise - 0.1Hz to 10Hz       -         Noise - 10Hz to 10kHz       20μVrms         Voltage - Input       -         Current - Supply       -         Current - Cathode       68μA         Operating Temperature       -40°C ~ 125°C (TA)         Mounting Type       Surface Mount         Package / Case       TO-236-3, SC-59, SOT-23-3         Supplier Device Package       SOT-23	Voltage - Output (Min/Fixed)	1.225V
Tolerance±0.5%Temperature Coefficient100ppm/°CNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz20μVrmsVoltage - Input-Current - Supply-Current - Cathode68μAOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Voltage - Output (Max)	-
Temperature Coefficient  Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  20μVrms  Voltage - Input  - Current - Supply  - Current - Cathode  68μA  Operating Temperature  -40°C ~ 125°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Current - Output	12mA
Noise - 0.1Hz to 10Hz       -         Noise - 10Hz to 10kHz       20μVrms         Voltage - Input       -         Current - Supply       -         Current - Cathode       68μA         Operating Temperature       -40°C ~ 125°C (TA)         Mounting Type       Surface Mount         Package / Case       TO-236-3, SC-59, SOT-23-3         Supplier Device Package       SOT-23	Tolerance	±0.5%
Noise - 10Hz to 10kHz20μVrmsVoltage - Input-Current - Supply-Current - Cathode68μAOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Temperature Coefficient	100ppm/°C
Voltage - Input-Current - Supply-Current - Cathode68μAOperating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Noise - 0.1Hz to 10Hz	-
Current - Supply-Current - Cathode $68\mu A$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23	Noise - 10Hz to 10kHz	20μVrms
Current - Cathode $68\mu A$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TA)  Mounting Type Surface Mount  Package / Case TO-236-3, SC-59, SOT-23-3  Supplier Device Package SOT-23	Voltage - Input	-
Operating Temperature  -40°C ~ 125°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package  SOT-23	Current - Supply	-
Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Current - Cathode	68μΑ
Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23	Operating Temperature	-40°C ~ 125°C (TA)
Supplier Device Package SOT-23	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Report errors?	Supplier Device Package	SOT-23
		Report errors?

#### **LM4041CFTA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **LM4041CFTA Payment Methods**



















## **LM4041CFTA Shipping Methods**













If you have any question about LM4041CFTA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com