



## LM431SBCM32X Information



For Reference Only

Part Number LM431SBCM32X

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

**Description**IC VREF SHUNT ADJ SOT23**Package**TO-236-3, SC-59, SOT-23-3

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# LM431SBCM32X Specifications

Manufacturer Part Number         LM431SBCM32X           Manufacturer         ON Semiconductor           Category         Integrated Circuits (ICs)           Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Adjustable           Voltage - Output (Min/Fixed)         2.495V           Voltage - Output (Max)         36V           Current - Output         100mA           Tolerance         ±1%           Temperature Coefficient         50ppm/°C Typical           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10Hz         -           Voltage - Input         -           Current - Supply         -           Current - Supply         -           Current - Cathode         ImA           Operating Temperature         -25°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23-3		
Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Adjustable           Voltage - Output (Min/Fixed)         2.495V           Voltage - Output (Max)         36V           Current - Output         100mA           Tolerance         ±1%           Temperature Coefficient         50ppm/°C Typical           Noise - 0.1Hz to 10Hz         -           Voltage - Input         -           Voltage - Input         -           Current - Supply         -           Current - Cathode         ImA           Operating Temperature         -25°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23-3	Manufacturer Part Number	LM431SBCM32X
Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Adjustable           Voltage - Output (Min/Fixed)         2.495 V           Voltage - Output (Max)         36 V           Current - Output         100mA           Tolerance         ±1%           Temperature Coefficient         50ppm/°C Typical           Noise - 0.1Hz to 10Hz         -           Voltage - Input         -           Current - Supply         -           Current - Cathode         ImA           Operating Temperature         -25°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23-3	Manufacturer	ON Semiconductor
Package         TO-236-3, SC-59, SOT-23-3           Series         -           Reference Type         Shunt           Output Type         Adjustable           Voltage - Output (Min/Fixed)         2.495 V           Voltage - Output (Max)         36 V           Current - Output         100mA           Tolerance         ±1%           Temperature Coefficient         50ppm/°C Typical           Noise - 0.1Hz to 10Hz         -           Noise - 10Hz to 10kHz         -           Voltage - Input         -           Current - Supply         -           Current - Cathode         ImA           Operating Temperature         -25°C ~ 85°C (TA)           Mounting Type         Surface Mount           Package / Case         TO-236-3, SC-59, SOT-23-3           Supplier Device Package         SOT-23-3	Category	Integrated Circuits (ICs)
Series-Reference TypeShuntOutput TypeAdjustableVoltage - Output (Min/Fixed)2.495 VVoltage - Output (Max)36 VCurrent - Output100mATolerance±1%Temperature Coefficient50ppm/°C TypicalNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - CathodeImAOperating Temperature-25°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3		PMIC - Voltage Reference
Reference TypeShuntOutput TypeAdjustableVoltage - Output (Min/Fixed)2.495 VVoltage - Output (Max)36 VCurrent - Output100mATolerance±1%Temperature Coefficient50ppm/°C TypicalNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - CathodeImAOperating Temperature-25°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Package	TO-236-3, SC-59, SOT-23-3
Output Type Adjustable  Voltage - Output (Min/Fixed) 2.495 V  Voltage - Output (Max) 36 V  Current - Output 100mA  Tolerance ±1%  Temperature Coefficient 50ppm/°C Typical  Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  Voltage - Input  Current - Supply  Current - Cathode 1mA  Operating Temperature25°C ~ 85°C (TA)  Mounting Type Surface Mount  Package / Case TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Series	-
Voltage - Output (Min/Fixed)  Voltage - Output (Max)  Current - Output  100mA  Tolerance  ±1%  Temperature Coefficient  Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  Voltage - Input  - Current - Supply  Current - Cathode  Operating Temperature  -25°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Reference Type	Shunt
Voltage - Output (Max)36VCurrent - Output100mATolerance±1%Temperature Coefficient50ppm/°C TypicalNoise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode1mAOperating Temperature-25°C ~ 85°C (TA)Mounting TypeSurface MountPackage / CaseTO-236-3, SC-59, SOT-23-3Supplier Device PackageSOT-23-3	Output Type	Adjustable
Current - Output  Tolerance  ±1%  Temperature Coefficient  Soppm/°C Typical  Noise - 0.1Hz to 10Hz  - Noise - 10Hz to 10kHz  - Voltage - Input  - Current - Supply  - Current - Cathode  ImA  Operating Temperature  Operating Type  Surface Mount  Package / Case  Supplier Device Package  100mA  100m	Voltage - Output (Min/Fixed)	2.495V
Tolerance ±1%  Temperature Coefficient 50ppm/°C Typical  Noise - 0.1Hz to 10Hz -  Noise - 10Hz to 10kHz -  Voltage - Input -  Current - Supply -  Current - Cathode ImA  Operating Temperature -25°C ~ 85°C (TA)  Mounting Type Surface Mount  Package / Case TO-236-3, SC-59, SOT-23-3  Supplier Device Package SOT-23-3	Voltage - Output (Max)	36V
Temperature Coefficient  Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  -  Voltage - Input  -  Current - Supply  -  Current - Cathode  Operating Temperature  -25°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Current - Output	100mA
Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  Voltage - Input  Current - Supply  Current - Cathode  Operating Temperature  Operating Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Tolerance	±1%
Noise - 10Hz to 10kHz -  Voltage - Input -  Current - Supply -  Current - Cathode 1mA  Operating Temperature -25°C ~ 85°C (TA)  Mounting Type Surface Mount  Package / Case TO-236-3, SC-59, SOT-23-3  Supplier Device Package SOT-23-3	Temperature Coefficient	50ppm/°C Typical
Voltage - Input  Current - Supply  - Current - Cathode  ImA  Operating Temperature  -25°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Noise - 0.1Hz to 10Hz	-
Current - Supply  Current - Cathode  ImA  Operating Temperature  -25°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package	Noise - 10Hz to 10kHz	-
Current - Cathode 1mA Operating Temperature -25°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23-3	Voltage - Input	-
Operating Temperature  -25°C ~ 85°C (TA)  Mounting Type  Surface Mount  Package / Case  TO-236-3, SC-59, SOT-23-3  Supplier Device Package  SOT-23-3	Current - Supply	-
Mounting Type Surface Mount Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23-3	Current - Cathode	1mA
Package / Case TO-236-3, SC-59, SOT-23-3 Supplier Device Package SOT-23-3	Operating Temperature	-25°C ~ 85°C (TA)
Supplier Device Package SOT-23-3	Mounting Type	Surface Mount
	Package / Case	TO-236-3, SC-59, SOT-23-3
Report errors?	Supplier Device Package	SOT-23-3
		Report errors?

#### LM431SBCM32X Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LM431SBCM32X Payment Methods



















### LM431SBCM32X Shipping Methods













If you have any question about LM431SBCM32X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com