

LP230-10B33

LP230-10B33 Information

Heisener.com	Part Number Manufacturer Category Description Package	LP230-10B33 Pulse Electronics Power Transformers Power Transformers XFRMR SEMI-TORO 2VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



LP230-10B33 Specifications

ManufacturerPulse Electronics PowerCategoryTransformersPackage-Package-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsVoltage - Isolation1500Vrms		
CategoryTransformersPackage-Package-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleSize / DimensionPC PinSize / Dimension6.51mmHeight - Seated (Max)1500VrmsWeight0.313 lb (141.97g)	Manufacturer Part Number	LP230-10B33
And getPower TransformersPackage-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsWeight0.313 lb (141.97g)	Manufacturer	Pulse Electronics Power
Package-SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension16.51mmVoltage - Isolation1500VrmsWeight0.313 Ib (141.97g)	Category	Transformers
SeriesLow Profile Plug-InTypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension16.51mmHeight - Seated (Max)1500VrmsWotage - Isolation313 lb (141.97g)		Power Transformers
TypeSemi-ToroidalVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsWeight0.313 lb (141.97g)	Package	-
YIVoltage - Primary-Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsWoitge - Isolation0.313 lb (141.97g)	Series	Low Profile Plug-In
Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)1500VrmsVoltage - Isolation500VrmsWeight0.313 lb (141.97g)	Туре	Semi-Toroidal
Current - Output (Max)Parallel 20mA, Series 10mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Voltage - Primary	-
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Voltage - Secondary (Full Load)	Parallel 115V, Series 230V
Secondary Winding(s)DualCenter TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Current - Output (Max)	Parallel 20mA, Series 10mA
Center TapNoPower - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Primary Winding(s)	Dual
Power - Max2 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Secondary Winding(s)	Dual
Nounting TypeThrough HoleTermination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Center Tap	No
Termination StylePC PinSize / Dimension47.63mm L x 39.67mm WHeight - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Power - Max	2 VA
Size / Dimension 47.63mm L x 39.67mm W Height - Seated (Max) 16.51mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Mounting Type	Through Hole
Height - Seated (Max)16.51mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Termination Style	PC Pin
Voltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Size / Dimension	47.63mm L x 39.67mm W
Weight 0.313 lb (141.97g)	Height - Seated (Max)	16.51mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.313 lb (141.97g)
		Report errors?

LP230-10B33 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

LP230-10B33 Payment Methods



LP230-10B33 Shipping Methods



If you have any question about LP230-10B33, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com