

LS2007.5/L Information

Heisener.com

Part Number LS2007.5/L

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 7.5V 200W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LS2007.5/L Specifications

Manufacturer Part Number LS2007.5/L Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LS200 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 26.7A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.83" L x 3.86" W x 1.61" H (199.0mm x 98.0mm x 41.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series LS200 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 26.7A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Manufacturer Part Number	LS2007.5/L
Package - Series LS200 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 26.7A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC	Manufacturer	TDK-Lambda Americas Inc.
Package - LS200 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 26.7A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Category	Power Supplies - External/Internal (Off-Board)
SeriesLS200TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 17.5VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)26.7APower (Watts)200WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency77%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesDC Input Capable, Remote On/Off, Remote Sense, Universal InputMounting TypeChassis Mount		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 26.7A Power (Watts) 200W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Package	-
Number of Outputs Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Series	LS200
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 7.5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Туре	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Voltage - Isolation ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation SkV (3000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Voltage - Output 1	7.5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Current - Output (Max)	26.7A
Voltage - Isolation 3kV (3000V) Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Power (Watts)	200W
Efficiency 77% Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Applications	ITE (Commercial)
Operating Temperature -25°C ~ 70°C (With Derating) Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, Remote On/Off, Remote Sense, Universal Input Mounting Type Chassis Mount	Efficiency	77%
Mounting Type Chassis Mount	Operating Temperature	-25°C ~ 70°C (With Derating)
	Features	DC Input Capable, Remote On/Off, Remote Sense, Universal Input
Size / Dimension 7.83" L x 3.86" W x 1.61" H (199.0mm x 98.0mm x 41.0mm)	Mounting Type	Chassis Mount
	Size / Dimension	7.83" L x 3.86" W x 1.61" H (199.0mm x 98.0mm x 41.0mm)
Report errors		Report errors?

LS2007.5/L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LS2007.5/L Payment Methods



















LS2007.5/L Shipping Methods













If you have any question about LS2007.5/L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com