

# LTC6655BHLS8-4.096#PBF

### LTC6655BHLS8-4.096#PBF Information



For Reference Only

Part Number LTC6655BHLS8-4.096#PBF

Manufacturer Linear Technology

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

**Description** IC VREF SERIES 4.096V 8LCC

Package 8-CLCC

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## LTC6655BHLS8-4.096#PBF Specifications

Manufacturer Part Number         LTC6655BHLS8-4.096#PBF           Manufacturer         Linear Technology           Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         8-CLCC           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096 V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.025%           Temperature Coefficient         2ppm/°C           Noise - 0.1Hz to 10Hz         0.25ppmp-p           Noise - 10Hz to 10kHz         -           Voltage - Input         4.596 V ~ 13.2 V           Current - Supply         7.5mA           Current - Cathode         -           Operating Temperature         40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         8-CLCC           Supplier Device Package         8-CLCC (5x5)		
Category         Integrated Circuits (ICs)           PMIC - Voltage Reference           Package         8-CLCC           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.025%           Temperature Coefficient         2ppm/°C           Noise - 0.1Hz to 10Hz         0.25ppmp-p           Noise - 10Hz to 10kHz         -           Voltage - Input         4.596 V ~ 13.2 V           Current - Supply         7.5mA           Current - Cathode         -           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         8-CLCC           Supplier Device Package         8-CLCC (5x5)	Manufacturer Part Number	LTC6655BHLS8-4.096#PBF
Package         8-CLCC           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.025%           Temperature Coefficient         2ppm/°C           Noise - 0.1Hz to 10Hz         0.25pmp-p           Noise - 10Hz to 10kHz         -           Voltage - Input         4.596 V ~ 13.2 V           Current - Supply         7.5mA           Current - Cathode         -           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         8-CLCC           Supplier Device Package         8-CLCC (5x5)	Manufacturer	Linear Technology
Package         8-CLCC           Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.025%           Temperature Coefficient         2ppm/°C           Noise - 0.1Hz to 10Hz         0.25ppmp-p           Noise - 10Hz to 10kHz         -           Voltage - Input         4.596 V ~ 13.2 V           Current - Supply         7.5mA           Current - Cathode         -           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         8-CLCC           Supplier Device Package         8-CLCC (5x5)	Category	Integrated Circuits (ICs)
Series         -           Reference Type         Series           Output Type         Fixed           Voltage - Output (Min/Fixed)         4.096V           Voltage - Output (Max)         -           Current - Output         5mA           Tolerance         ±0.025%           Temperature Coefficient         2ppm/°C           Noise - 0.1Hz to 10Hz         0.25ppmp-p           Noise - 10Hz to 10kHz         -           Voltage - Input         4.596 V ~ 13.2 V           Current - Supply         7.5mA           Current - Cathode         -           Operating Temperature         -40°C ~ 125°C (TA)           Mounting Type         Surface Mount           Package / Case         8-CLCC           Supplier Device Package         8-CLCC (5x5)		PMIC - Voltage Reference
Reference TypeSeriesOutput TypeFixedVoltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output5mATolerance±0.025%Temperature Coefficient2ppm/°CNoise - 0.1Hz to 10Hz0.25ppmp-pNoise - 10Hz to 10kHz-Voltage - Input4.596 V ~ 13.2 VCurrent - Supply7.5mACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case8-CLCCSupplier Device Package8-CLCC (5x5)	Package	8-CLCC
Output Type Fixed  Voltage - Output (Min/Fixed) 4.096V  Voltage - Output (Max) - Current - Output 5mA  Tolerance ±0.025%  Temperature Coefficient 2ppm/°C  Noise - 0.1Hz to 10Hz 0.25ppmp-p  Noise - 10Hz to 10kHz - Voltage - Input 4.596 V ~ 13.2 V  Current - Supply 7.5mA  Current - Cathode - Operating Temperature 40°C ~ 125°C (TA)  Mounting Type Surface Mount  Package / Case 8-CLCC  Supplier Device Package 8-CLCC (5x5)	Series	-
Voltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output5mATolerance±0.025%Temperature Coefficient2ppm/°CNoise - 0.1Hz to 10Hz0.25ppmp-pNoise - 10Hz to 10kHz-Voltage - Input4.596 V ~ 13.2 VCurrent - Supply7.5mACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case8-CLCCSupplier Device Package8-CLCC (5x5)	Reference Type	Series
Voltage - Output (Max)  Current - Output  5mA  Tolerance  ±0.025%  Temperature Coefficient  2ppm/°C  Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  - Voltage - Input  4.596 V ~ 13.2 V  Current - Supply  7.5mA  Current - Cathode  - Operating Temperature  40°C ~ 125°C (TA)  Mounting Type  Surface Mount  Package / Case  Supplier Device Package  8-CLCC  5mA	Output Type	Fixed
Current - Output  Tolerance  ±0.025%  Temperature Coefficient  2ppm/°C  Noise - 0.1Hz to 10Hz  0.25ppmp-p  Noise - 10Hz to 10kHz  -  Voltage - Input  4.596 V ~ 13.2 V  Current - Supply  7.5mA  Current - Cathode  -  Operating Temperature  4.0°C ~ 125°C (TA)  Mounting Type  Surface Mount  Package / Case  Supplier Device Package  8-CLCC  8-CLCC (5x5)	Voltage - Output (Min/Fixed)	4.096V
Tolerance ±0.025%  Temperature Coefficient 2ppm/°C  Noise - 0.1Hz to 10Hz 0.25ppmp-p  Noise - 10Hz to 10kHz  Voltage - Input 4.596 V ~ 13.2 V  Current - Supply 7.5mA  Current - Cathode  Operating Temperature -40°C ~ 125°C (TA)  Mounting Type Surface Mount  Package / Case 8-CLCC  Supplier Device Package 8-CLCC (5x5)	Voltage - Output (Max)	-
Temperature Coefficient  Noise - 0.1Hz to 10Hz  0.25ppmp-p  Noise - 10Hz to 10kHz  - Voltage - Input  4.596 V ~ 13.2 V  Current - Supply  7.5mA  Current - Cathode  Operating Temperature  -40°C ~ 125°C (TA)  Mounting Type  Surface Mount  Package / Case  8-CLCC  Supplier Device Package	Current - Output	5mA
Noise - 0.1Hz to 10Hz  Noise - 10Hz to 10kHz  -  Voltage - Input  4.596 V ~ 13.2 V  Current - Supply  7.5mA  Current - Cathode  -  Operating Temperature  -40°C ~ 125°C (TA)  Mounting Type  Surface Mount  Package / Case  8-CLCC  Supplier Device Package	Tolerance	±0.025%
Noise - 10Hz to 10kHz - 4.596 V ~ 13.2 V  Current - Supply 7.5mA  Current - Cathode -  Operating Temperature -40°C ~ 125°C (TA)  Mounting Type Surface Mount  Package / Case 8-CLCC  Supplier Device Package 8-CLCC (5x5)	Temperature Coefficient	2ppm/°C
Voltage - Input4.596 V ~ 13.2 VCurrent - Supply7.5mACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case8-CLCCSupplier Device Package8-CLCC (5x5)	Noise - 0.1Hz to 10Hz	0.25ppmp-p
Current - Supply 7.5mA  Current - Cathode -  Operating Temperature -40°C ~ 125°C (TA)  Mounting Type Surface Mount  Package / Case 8-CLCC  Supplier Device Package 8-CLCC (5x5)	Noise - 10Hz to 10kHz	-
Current - Cathode	Voltage - Input	4.596 V ~ 13.2 V
Operating Temperature -40°C ~ 125°C (TA)  Mounting Type Surface Mount  Package / Case 8-CLCC  Supplier Device Package 8-CLCC (5x5)	Current - Supply	7.5mA
Mounting Type Surface Mount Package / Case 8-CLCC Supplier Device Package 8-CLCC (5x5)	Current - Cathode	-
Package / Case 8-CLCC Supplier Device Package 8-CLCC (5x5)	Operating Temperature	-40°C ~ 125°C (TA)
Supplier Device Package 8-CLCC (5x5)	Mounting Type	Surface Mount
	Package / Case	8-CLCC
	Supplier Device Package	8-CLCC (5x5)
Report errors?		Report errors?

#### LTC6655BHLS8-4.096#PBF Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### LTC6655BHLS8-4.096#PBF Payment Methods





















## LTC6655BHLS8-4.096#PBF Shipping Methods













If you have any question about LTC6655BHLS8-4.096#PBF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com