



LXV150-054SW Information

Part Number LXV150-054SW

Manufacturer Excelsys Technologies Ltd

Power Supplies - External/Internal (Off-Board) Category

LED Drivers

Description LED DRIVER CV AC/DC 54V 2.78A

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LXV150-054SW Specifications

Manufacturer Part Number LXV150-054SW Manufacturer Excelsys Technologies Ltd Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXV150 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series LXV150 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Output (Max) 305VAC Voltage - Output (Max) 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Manufacturer Part Number	LXV150-054SW	
Package - Series LXV150 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Manufacturer	Excelsys Technologies Ltd	
Package - Series LXV150 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series LXV150 Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)		LED Drivers	
Type Constant Voltage Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Series	LXV150	
Number of Outputs 1 Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Туре	Constant Voltage	
Voltage - Input (Min) 90VAC Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Topology	AC DC Converter	
Voltage - Input (Max) 305VAC Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Number of Outputs	1	
Voltage - Output 54V Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Input (Min)	90VAC	
Current - Output (Max) 2.78A Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Input (Max)	305VAC	
Power (Watts) 150W Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Output	54V	
Voltage - Isolation 3.75kV (3750V) Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Current - Output (Max)	2.78A	
Dimming - Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Power (Watts)	150W	
Features OCP, OTP, OVP, SCP Ratings IP67 Operating Temperature -35°C ~ 70°C Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Voltage - Isolation	3.75kV (3750V)	
Ratings IP67 Operating Temperature $-35^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Dimming	-	
Operating Temperature $-35^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Features	OCP, OTP, OVP, SCP	
Efficiency 93% Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Ratings	IP67	
Termination Style Wire Leads Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Operating Temperature	-35°C ~ 70°C	
Size / Dimension 7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	Efficiency	93%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	7.84" L x 2.66" W x 1.58" H (199.0mm x 67.5mm x 40.0mm)	
			Report errors?

LXV150-054SW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LXV150-054SW Payment Methods



















LXV150-054SW Shipping Methods













If you have any question about LXV150-054SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com