



M2023SS1W01-BA Information

Heisener.com

For Reference Only

Part Number M2023SS1W01-BA

Manufacturer NKK Switches

Switches

Category

Toggle Switches

Description

SWITCH TOGGLE DPDT 6A 125V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2023SS1W01-BA Specifications

Manufacturer Part NumberM2023SSIW01-BAManufacturerNKK SwitchesCategorySwitchesPackage-SeriesMCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-		
CategorySwitchesPackage-SeriesMCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Manufacturer Part Number	M2023SS1W01-BA
Package - Circuit DPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated 118umination Type, Color - Illumination Voltage (Nominal) - Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Circular - 6.50mm Dia	Manufacturer	NKK Switches
Package-SeriesMCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Category	Switches
SeriesMCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Package	-
Switch Function Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Sushing Thread Ingress Protection On-Off-On 6A (AC), 3A (DC) 125V 30V Standard Round with Cap Standard Round with Cap Actuator Length 13.50mm Non-Illuminated 13.50mm Son-Illuminated 13.50mm Circular - 6.50mm Dia 14-40 Ingress Protection -	Series	M
Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection 125V 30V Actuator Length 13.50mm Non-Illuminated - Panel Mount Circular - 6.50mm Dia 1/4-40 Ingress Protection -	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection - 30V 30V 30V 30V 30V 500 Standard Round with Cap 13.50mm Non-Illuminated Panel Mount Solder Lug Solder Lug	Current Rating	6A (AC), 3A (DC)
Actuator Type Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Standard Round with Cap 13.50mm Non-Illuminated Panel Mount Circular - 6.50mm Dia	Voltage Rating - AC	125V
Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection	Actuator Type	Standard Round with Cap
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Actuator Length	13.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection -	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	Circular - 6.50mm Dia
	Bushing Thread	1/4-40
	Ingress Protection	-
Features Black Cap	Features	Black Cap
Report errors?		Report errors?

M2023SS1W01-BA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2023SS1W01-BA Payment Methods





















M2023SS1W01-BA Shipping Methods













If you have any question about M2023SS1W01-BA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com