



M5254-000005-01KPG Information

Part Number M5254-000005-01KPG

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

Description TRANSDUCER

Package Cylinder

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M5254-000005-01KPG Specifications

Manufacturer Part Number M5254-00005-01 KPG Manufacturer TE Connectivity Measurement Specialties Category Sensors, Transducers Package Cylinder Series M5200 Pressure Type Vented Gauge Operating Pressure 1000 PSI (6894.76 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Thereaded Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinderSeriesM5200Pressure TypeVented GaugeOperating Pressure1000 PSI (6894.76 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure2000 PSI (13789.51 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	M5254-000005-01KPG
Package Cylinder Series M5200 Pressure Type Vented Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Tempination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder Supplier Device Package Cylinder Cylinder Cylinder M5200 Vonted Gauge 1000 PSI (6894.76 kPa) Analog Current 4 mA ~ 20 mA 7	Manufacturer	TE Connectivity Measurement Specialties
Package Cylinder Series M5200 Pressure Type Vented Gauge Operating Pressure 1000 PSI (6894.76 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Category	Sensors, Transducers
SeriesM5200Pressure TypeVented GaugeOperating Pressure1000 PSI (6894.76 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure2000 PSI (13789.51 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure1000 PSI (6894.76 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure2000 PSI (13789.51 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 1000 PSI (6894.76 kPa) Analog Current A mA ~ 20 mA -40 mA	Series	M5200
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure2000 PSI (13789.51 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Vented Gauge
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure $2000 \text{ PSI } (13789.51 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Operating Pressure	1000 PSI (6894.76 kPa)
Accuracy ±0.25% Voltage - Supply 9 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Output Type	Analog Current
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	9 V ~ 30 V
Features Temperature Compensated Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Connector Maximum Pressure 2000 PSI (13789.51 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure2000 PSI (13789.51 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	2000 PSI (13789.51 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

M5254-000005-01KPG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M5254-000005-01KPG Payment Methods



















M5254-000005-01KPG Shipping Methods













If you have any question about M5254-000005-01KPG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com