

**M80-8281442 Information**


For Reference Only

**Part Number** [M80-8281442](#)
**Manufacturer** Harwin Inc.

**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)
**Description** CONN HDR 2MM SMT W/LATCH 14POS

**Package** -

For the pricing/inventory/lead time, please contact us

 Website: <https://www.heisener.com>

 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)

[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**M80-8281442 Specifications**

|                            |                                                                                          |
|----------------------------|------------------------------------------------------------------------------------------|
| Manufacturer Part Number   | <a href="#">M80-8281442</a>                                                              |
| Manufacturer               | Harwin Inc.                                                                              |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -                                                                                        |
| Series                     | Datamate L-Tek                                                                           |
| Connector Type             | Header                                                                                   |
| Contact Type               | Male Pin                                                                                 |
| Pitch - Mating             | 0.079" (2.00mm)                                                                          |
| Style                      | Board to Board or Cable                                                                  |
| Shrouding                  | Shrouded - 4 Wall                                                                        |
| Number of Positions        | 14                                                                                       |
| Number of Positions Loaded | All                                                                                      |
| Number of Rows             | 2                                                                                        |
| Row Spacing - Mating       | 0.079" (2.00mm)                                                                          |
| Mounting Type              | Surface Mount                                                                            |
| Termination                | Solder                                                                                   |
| Fastening Type             | Latch Lock                                                                               |
| Contact Length - Mating    | -                                                                                        |
| Contact Length - Post      | -                                                                                        |
| Overall Contact Length     | -                                                                                        |
| Insulation Height          | 0.205" (5.20mm)                                                                          |
| Contact Shape              | Circular                                                                                 |
| Contact Finish - Mating    | Gold                                                                                     |

|                                   |                                           |
|-----------------------------------|-------------------------------------------|
| Contact Finish Thickness - Mating | 29.5μin (0.75μm)                          |
| Contact Finish - Post             | Tin                                       |
| Contact Material                  | Phosphor Bronze                           |
| Insulation Material               | Polyphenylene Sulfide (PPS), Glass Filled |
| Features                          | -                                         |
| Operating Temperature             | -55°C ~ 125°C                             |
| Ingress Protection                | -                                         |
| Material Flammability Rating      | UL94 V-0                                  |
| Insulation Color                  | Black                                     |
| <a href="#">Report errors?</a>    |                                           |

## M80-8281442 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## M80-8281442 Payment Methods



## M80-8281442 Shipping Methods



If you have any question about M80-8281442, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)